
python_ics Documentation

Release 2.5

David Rebbe

May 30, 2018

Contents

1 Variables	33
2 Indices and tables	45
Python Module Index	47

Python C Code module for interfacing to the icsneo40 dynamic library. Code tries to respect PEP 8 (<http://python.org/dev/peps/pep-0008>). Function naming convention does not follow the tradition c style icsneo40 naming convention as pyics module name acts as the namespace (icsneo portion of the function) and function names are suppose to be lowercase with underscores instead of mixedCase like icsneo API.

C API can be mimiced almost identically by doing the following:

```
>>> import ics as icsneo
>>> devices = icsneo.FindNeoDevices()
>>> for device in devices:
...     print(device.Name, device.SerialNumber)
...
neoVI FIRE 59886
```

Recommended Python way by doing the following:

```
>>> import ics
>>> devices = ics.find_devices()
>>> for device in devices:
...     print(device.Name, device.SerialNumber)
...
neoVI FIRE 59886
```

It should be noted that `ics.NeoDevice` is used a little bit differently than the C API. `ics.NeoDevice` contains two extra members:

`ics.NeoDevice.AutoHandleClose` and `ics.NeoDevice._Handle`

The handle normally returned from `icsneoOpenNeoDevice()` is stored inside `_Handle` and setting `AutoHandleClose` to True (Default) will automatically close the handle when the `ics.NeoDevice` goes out of scope.

Installation:

`pip install python_ics`

<https://pypi.python.org/pypi/python-ics>

```
exception ics.ArgumentError
    Bases: Exception

exception ics.RuntimeError
    Bases: Exception

class ics.ApiFirmwareInfo
    Bases: object

    ApiFirmwareInfo object

    iAppMajor
    iAppMinor
    iBoardRevMajor
    iBoardRevMinor
    iBootLoaderVersionMajor
    iBootLoaderVersionMinor
    iMainFirmChkSum
    iMainFirmDateDay
    iMainFirmDateHour
```

```
iMainFirmDateMin
iMainFirmDateMonth
iMainFirmDateSecond
iMainFirmDateYear
iMainVnetHWrevMajor
iMainVnetHWrevMinor
iMainVnetSRAMSize
iManufactureDay
iManufactureMonth
iManufactureYear
iType

class ics.CanFdSettings
Bases: object
CanFdSettings object

FDBRP
FDBaudrate
FDMode
FDTqProp
FDTqSeg1
FDTqSeg2
FDTqSync

class ics.CanSettings
Bases: object
CanSettings object

BRP
Baudrate
The bit rate of a CAN channel can be selected from a list of common bit rates Write the correct enumeration
for the desired bit rate and ensure that SetBaudrate is 1(auto)

Mode
CAN controller mode when the neoVI device goes online or runs a CoreMini script. Normal=0 Disabled=1
Listen Only=3 Listen All=7

SetBaudrate
The bit rate of a CAN channel can be selected one of two ways. It can either be selected from a list of
common bit rates (SetBaudrate=1) or the user can specify the CAN timing parameters (SetBaudrate=0)

TqProp
Propagation delay

TqSeg1
Phase 1 segment

TqSeg2
Phase 2 segment
```

TqSync
Syncro jump width

auto_baud
Enables the auto bitrate feature. 1 = enable, 0 = disable.

innerFrameDelay25us

transceiver_mode
Currently Not used.

class ics.CyanSettings
Bases: object

CyanSettings object

ain_sample_period

ain_threshold

can1
ics.CanSettings Object

can2
ics.CanSettings Object

can3
ics.CanSettings Object

can4
ics.CanSettings Object

can5
ics.CanSettings Object

can6
ics.CanSettings Object

can7
ics.CanSettings Object

can8
ics.CanSettings Object

can_switch_mode

canfd1
ics.CanFdSettings Object

canfd2
ics.CanFdSettings Object

canfd3
ics.CanFdSettings Object

canfd4
ics.CanFdSettings Object

canfd5
ics.CanFdSettings Object

canfd6
ics.CanFdSettings Object

```
canfd7
    ics.CanFdSettings Object

canfd8
    ics.CanFdSettings Object

digitalIoThresholdEnable

digitalIoThresholdTicks

disableUsbCheckOnBoot

enableLatencyTest

ethernet
    ics.EthernetSettings Object

idle_wakeup_network_enables_3

iso15765_separation_time_offset

iso9141_kwp_settings_1
    Iso9141Keyword2000Settings Object

iso9141_kwp_settings_2
    Iso9141Keyword2000Settings Object

iso9141_kwp_settings_3
    Iso9141Keyword2000Settings Object

iso9141_kwp_settings_4
    Iso9141Keyword2000Settings Object

iso_msg_termination_1
    0 - use inner frame time, 1 - GME CIM-SCL

iso_msg_termination_2
    0 - use inner frame time, 1 - GME CIM-SCL

iso_msg_termination_3
    0 - use inner frame time, 1 - GME CIM-SCL

iso_msg_termination_4
    0 - use inner frame time, 1 - GME CIM-SCL

iso_parity_1
    0 - no parity, 1 - event, 2 - odd

iso_parity_2
    0 - no parity, 1 - event, 2 - odd

iso_parity_3
    0 - no parity, 1 - event, 2 - odd

iso_parity_4
    0 - no parity, 1 - event, 2 - odd

lin1
    ics.LinSettings Object

lin2
    ics.LinSettings Object

lin3
    ics.LinSettings Object
```

```
lin4
    ics.LinSettings Object

lin5
    ics.LinSettings Object

lin6
    ics.LinSettings Object

lsft1
    ics.CanSettings Object

lsft2
    ics.CanSettings Object

misc_io_analog_enable
misc_io_initial_ddr
misc_io_initial_latch
misc_io_on_report_events
misc_io_report_period
network_enabled_on_boot
network_enables
network_enables_2
network_enables_3
perf_en
pwr_man_enable
pwr_man_timeout
reserved
slaveVnetA
slaveVnetB

swcan1
    ics.SWCanSettings Object

swcan2
    ics.SWCanSettings Object

termination_enables
text_api
    ics.TextApiSettings Object

class ics.EthernetSettings
Bases: object
EthernetSettings object

auto_neg
duplex
led_mode
link_speed
```

```
rsvd
class ics.FireSettings
    Bases: object

    FireSettings object

    ain_sample_period
    ain_threshold
    can1
        ics.CanSettings Object
    can2
        ics.CanSettings Object
    can3
        ics.CanSettings Object
    can4
        ics.CanSettings Object

    cgi_baud
    cgi_chksum_enable
    cgi_enable_reserved
    cgi_rx_ifs_bit_times
    cgi_tx_ifs_bit_times
    fast_init_network_enables_1
    fast_init_network_enables_2
    iso15765_separation_time_offset
    iso9141_kwp_enable_reserved
    iso9141_kwp_settings
        Iso9141Keyword2000Settings Object
    iso9141_kwp_settings_2
        Iso9141Keyword2000Settings Object
    iso9141_kwp_settings_3
        Iso9141Keyword2000Settings Object
    iso9141_kwp_settings_4
        Iso9141Keyword2000Settings Object

    iso_msg_termination
        0 - use inner frame time, 1 - GME CIM-SCL
    iso_msg_termination_2
        0 - use inner frame time, 1 - GME CIM-SCL
    iso_msg_termination_3
        0 - use inner frame time, 1 - GME CIM-SCL
    iso_msg_termination_4
        0 - use inner frame time, 1 - GME CIM-SCL

    iso_parity
        0 - no parity, 1 - event, 2 - odd
```

```
iso_parity_2
    0 - no parity, 1 - event, 2 - odd

iso_parity_3
    0 - no parity, 1 - event, 2 - odd

iso_parity_4
    0 - no parity, 1 - event, 2 - odd

iso_tester_pullup_enable

lin1
    ics.LinSettings Object

lin2
    ics.LinSettings Object

lin3
    ics.LinSettings Object

lin4
    ics.LinSettings Object

lsft
    ics.CanSettings Object

misc_io_analog_enable

misc_io_initial_ddr

misc_io_initial_latch

misc_io_on_report_events

misc_io_report_period

network_enabled_on_boot

network_enables

network_enables_2

perf_en

pwm_man_timeout

pwr_man_enable

swcan
    ics.SWCanSettings Object

text_api
    ics.TextApiSettings Object

uart
    ics.UartSettings Object

uart2
    ics.UartSettings Object

vnetBits

class ics.Iso9141Keyword2000InitSteps
Bases: object

Iso9141Keyword2000InitSteps object
```

```
k
l
time_500us

class ics.Iso9141Keyword2000Settings
Bases: object
Iso9141Keyword2000Settings object

Baudrate
brgh
chksum_enabled
init_steps
    Tuple of Iso9141Keyword2000InitSteps
p2_500us
p3_500us
p4_500us
spbrg

class ics.LinSettings
Bases: object
LinSettings object

Baudrate
MasterResistor
Mode
brgh
spbrg

class ics.NeoDevice
Bases: object
NeoDevice object

AutoHandleClose
    When NeoDevice is freed the handle will automatically be closed, if true.

DeviceType
Handle
IsOpen
    This contains the handle returned from icsneoOpenDevice() API. If uncertain, don't use this.

MaxAllowedClients
Name
    String describing DeviceType, extension to Python api only.

NumberOfClients
SerialNumber
```

```
class ics.OpEthGeneralSettings
Bases: object

OpEthGeneralSettings object

bEnReportLinkQuality
bTapEnPtp
bTapEnSwitch
reserved0
tapPair0
tapPair1
tapPair2
tapPair3
tapPair4
tapPair5
ucInterfaceType

class ics.OpEthSettings
Bases: object

OpEthSettings object

preemption_en
reserved0
ucConfigMode

class ics.RadGalaxySettings
Bases: object

RadGalaxySettings object

ain_sample_period
ain_threshold
can1
    ics.CanSettings Object
can2
    ics.CanSettings Object
can3
    ics.CanSettings Object
can4
    ics.CanSettings Object
can5
    ics.CanSettings Object
can6
    ics.CanSettings Object
can7
    ics.CanSettings Object
```

```
can8
    ics.CanSettings Object

can_switch_mode

canfd1
    ics.CanFdSettings Object

canfd2
    ics.CanFdSettings Object

canfd3
    ics.CanFdSettings Object

canfd4
    ics.CanFdSettings Object

canfd5
    ics.CanFdSettings Object

canfd6
    ics.CanFdSettings Object

canfd7
    ics.CanFdSettings Object

canfd8
    ics.CanFdSettings Object

idle_wakeup_network_enables_1

idle_wakeup_network_enables_2

idle_wakeup_network_enables_3

iso15765_separation_time_offset

iso9141_kwp_settings_1
    Iso9141Keyword2000Settings Object

iso_msg_termination_1
    0 - use inner frame time, 1 - GME CIM-SCL

iso_parity_1
    0 - no parity, 1 - event, 2 - odd

lin1
    ics.LinSettings Object

misc_io_analog_enable

misc_io_initial_ddr

misc_io_initial_latch

misc_io_on_report_events

misc_io_report_period

network_enabled_on_boot

network_enables

network_enables_2

network_enables_3
```

```
opEth1
    ics.OpEthSettings Object

opEth10
    ics.OpEthSettings Object

opEth11
    ics.OpEthSettings Object

opEth12
    ics.OpEthSettings Object

opEth2
    ics.OpEthSettings Object

opEth3
    ics.OpEthSettings Object

opEth4
    ics.OpEthSettings Object

opEth5
    ics.OpEthSettings Object

opEth6
    ics.OpEthSettings Object

opEth7
    ics.OpEthSettings Object

opEth8
    ics.OpEthSettings Object

opEth9
    ics.OpEthSettings Object

opEthGen
    ics.OpEthGeneralSettings Object

perf_en

pwr_man_enable

pwr_man_timeout

swcan1
    ics.SWCanSettings Object

swcan2
    ics.SWCanSettings Object

text_api
    ics.TextApiSettings Object

class ics.SWCanSettings
    Bases: object

    SWCanSettings object

BRP

Baudrate
    The bit rate of a CAN channel can be selected from a list of common bit rates Write the correct enumeration
    for the desired bit rate and ensure that SetBaudrate is 1(auto)
```

Mode

CAN controller mode when the neoVI device goes online or runs a CoreMini script. Normal=0 Disabled=1 Listen Only=3 Listen All=7

RESERVED

SetBaudrate

The bit rate of a CAN channel can be selected one of two ways. It can either be selected from a list of common bit rates (SetBaudrate=1) or the user can specify the CAN timing parameters (SetBaudrate=0)

TqProp

Propagation delay

TqSeg1

Phase 1 segment

TqSeg2

Phase 2 segment

TqSync

Syncro jump width

auto_baud

Enables the auto bitrate feature. 1 = enable, 0 = disable.

high_speed_auto_switch

transceiver_mode

Currently Not used.

class ics.SpyMessage

Bases: object

SpyMessage object

AckBytes

ArbIDOrHeader

Data

DescriptionID

Not Used

ExtraDataPtr

ExtraDataPtrEnabled

MessagePieceID

Not Used

MiscData

NetworkID

This value is used to identify which network this message was received on.

NodeID

Not Used

NumberBytesData

Holds the number of bytes in the Data(1 to 8) array or the number of bytes in a CAN remote frame (The DLC).

NumberBytesHeader

Used for J1850/ISO messages. It indicates how many bytes are stored in the Header(1 to 4) array.

Protocol

Valid values are SPY_PROTOCOL_CAN, SPY_PROTOCOL_J1850VPW, and SPY_PROTOCOL_ISO9141.

StatusBitField**StatusBitField2****StatusBitField3****StatusBitField4****TimeHardware**

Hardware time stamp. The TimeStamp is reset on device open

TimeHardware2

Hardware time stamp. The TimeStamp is reset on device open

TimeStampHardwareID

This is an identifier of what type of hardware timestamp is used. Since neoVI's timestamp is always the same, this doesn't change.

TimeStampSystemID

This is an identifier of what type of system timestamp is used. Since WIN32 neoVI's timestamp is always the same, from the timeGetTime API, this doesn't change.

TimeSystem

TimeSystem is loaded with the value received from the timeGetTime call in the WIN32 multimedia API.

TimeSystem2

TimeSystem is loaded with the value received from the timeGetTime call in the WIN32 multimedia API.

noExtraDataPtrCleanup

Tells Python to not clean up ExtraDataPtrMemory, If this is enabled. Ignore, if unsure.

class ics.SpyMessageJ1850

Bases: object

SpyMessageJ1850 object

AckBytes**Data****DescriptionID**

Not Used

ExtraDataPtr**ExtraDataPtrEnabled****Header****MessagePieceID**

Not Used

MiscData**NetworkID**

This value is used to identify which network this message was received on.

NodeID

Not Used

NumberBytesData

Holds the number of bytes in the Data(1 to 8) array or the number of bytes in a CAN remote frame (The DLC).

NumberBytesHeader

Used for J1850/ISO messages. It indicates how many bytes are stored in the Header(1 to 4) array.

Protocol

Valid values are SPY_PROTOCOL_CAN, SPY_PROTOCOL_J1850VPW, and SPY_PROTOCOL_ISO9141.

StatusBitField

StatusBitField2

StatusBitField3

StatusBitField4

TimeHardware

Hardware time stamp. The TimeStamp is reset on device open

TimeHardware2

Hardware time stamp. The TimeStamp is reset on device open

TimeStampHardwareID

This is an identifier of what type of hardware timestamp is used. Since neoVI's timestamp is always the same, this doesn't change.

TimeStampSystemID

This is an identifier of what type of system timestamp is used. Since WIN32 neoVI's timestamp is always the same, from the timeGetTime API, this doesn't change.

TimeSystem

TimeSystem is loaded with the value received from the timeGetTime call in the WIN32 multimedia API.

TimeSystem2

TimeSystem is loaded with the value received from the timeGetTime call in the WIN32 multimedia API.

noExtraDataPtrCleanup

Tells Python to not clean up ExtraDataPtrMemory, If this is enabled. Ignore, if unsure.

class ics.TextApiSettings

Bases: object

TextApiSettings object

can1_options

Sets the length of the Arbitration ID's. Set to 1 for Extended and 0 for Standard

can1_rx_id

Sets or Reads the Arbitration ID for Sending Receiving API commands

can1_tx_id

Sets or Reads the Arbitration ID for Sending Text API commands

can2_options

can2_rx_id

can2_tx_id

can3_options

can3_rx_id

```
can3_tx_id
can4_options
can4_rx_id
can4_tx_id
network_enables
    Bitfield telling which netowrk to support Text API.

class ics.UartSettings
Bases: object
UartSettings object

Baudrate
    Holds the baud rate for the UART Connection. An example value could be 10417 or 9600

bOptions
    Bitfield containing UART Options Invert TX=1, Invert RX=2, Half Duplex=4

brgh

flow_control
    Set to 0 for no flow control and 1 for simple CTS RTS

parity
    Sets the Parity type. Valid values are None=0, Even=1, Odd=2

reserved_1

spbrg

stop_bits
    Sets the number of stop bits to use. Valid values are One=1, Two=2

class ics.Vcan3Settings
Bases: object
Vcan3Settings object

can1
    ics.CanSettings Object

can2
    ics.CanSettings Object

iso15765_separation_time_offset

misc_io_initial_ddr

misc_io_initial_latch

misc_io_on_report_events

misc_io_report_period

network_enabled_on_boot

network_enables

perf_en

class ics.VcanRFSettings
Bases: object
VcanRFSettings object
```

```
can1
    ics.CanSettings Object

can2
    ics.CanSettings Object

can3
    ics.CanSettings Object

can4
    ics.CanSettings Object

idle_wakeup_network_enables_1
idle_wakeup_network_enables_2
iso15765_separation_time_offset
iso9141_kwp_enable_reserved
iso9141_kwp_settings
    ics.Iso9141Keyword2000Settings Object
iso9141_kwp_settings_2
    ics.Iso9141Keyword2000Settings Object

iso_msg_termination
    0 - use inner frame time, 1 - GME CIM-SCL
iso_msg_termination_2
    0 - use inner frame time, 1 - GME CIM-SCL

iso_parity
    0 - no parity, 1 - event, 2 - odd
iso_parity_2
    0 - no parity, 1 - event, 2 - odd

iso_tester_pullup_enable

lin1
    ics.LinSettings Object

lin2
    ics.LinSettings Object

misc_io_analog_enable
misc_io_initial_ddr
misc_io_initial_latch
misc_io_on_report_events
misc_io_report_period
network_enabled_on_boot
network_enables
network_enables_2
perf_en
pwr_man_enable
    0 - off, 1 - sleep enabled, 2- idle enabled (fast wakeup)
```

```
pwr_man_timeout  
ics.ClosePort()
```

Note: Identical to PEP8 compliant `ics.close_device()` method.

```
ics.FindNeoDevices()
```

Note: Identical to PEP8 compliant `ics.find_devices()` method.

```
ics.GetDLLVersion()
```

Note: Identical to PEP8 compliant `ics.get_dll_version()` method.

```
ics.GetErrorMessages()
```

Note: Identical to PEP8 compliant `ics.get_error_messages()` method.

```
ics.GetHWFirmwareInfo()
```

Note: Identical to PEP8 compliant `ics.get_hw_firmware_info()` method.

```
ics.GetLastError()
```

Note: Identical to PEP8 compliant `ics.get_last_api_error()` method.

```
ics.GetMessages()
```

Note: Identical to PEP8 compliant `ics.get_messages()` method.

```
ics.GetPerformanceParameters()
```

Note: Identical to PEP8 compliant `ics.get_performance_parameters()` method.

```
ics.GetRTC()
```

Note: Identical to PEP8 compliant `ics.get_rtc()` method.

`ics.GetSerialNumber()`

Note: Identical to PEP8 compliant `ics.get_serial_number()` method.

`ics.OpenNeoDevice()`

Note: Identical to PEP8 compliant `ics.open_device()` method.

`ics.RequestEnterSleepMode()`

Note: Identical to PEP8 compliant `ics.request_enter_sleep_mode()` method.

`ics.ScriptClear()`

Note: Identical to PEP8 compliant `ics.coremini_clear()` method.

`ics.ScriptGetFBlockStatus()`

Note: Identical to PEP8 compliant `ics.coremini_get_fblock_status()` method.

`ics.ScriptGetScriptStatus()`

Note: Identical to PEP8 compliant `ics.coremini_get_status()` method.

`ics.ScriptLoad()`

Note: Identical to PEP8 compliant `ics.coremini_load()` method.

`ics.ScriptReadAppSignal()`

Note: Identical to PEP8 compliant `ics.coremini_read_app_signal()` method.

`ics.ScriptReadRxMessage()`

Note: Identical to PEP8 compliant `ics.coremini_read_rx_message()` method.

`ics.ScriptReadTxMessage()`

Note: Identical to PEP8 compliant `ics.coremini_read_tx_message()` method.

`ics.ScriptStart()`

Note: Identical to PEP8 compliant `ics.coremini_start()` method.

`ics.ScriptStartFBlock()`

Note: Identical to PEP8 compliant `ics.coremini_start_fblock()` method.

`ics.ScriptStop()`

Note: Identical to PEP8 compliant `ics.coremini_stop()` method.

`ics.ScriptStopFBlock()`

Note: Identical to PEP8 compliant `ics.coremini_stop_fblock()` method.

`ics.ScriptWriteAppSignal()`

Note: Identical to PEP8 compliant `ics.coremini_write_app_signal()` method.

`ics.ScriptWriteRxMessage()`

Note: Identical to PEP8 compliant `ics.coremini_write_rx_message()` method.

`ics.ScriptWriteTxMessage()`

Note: Identical to PEP8 compliant `ics.coremini_write_tx_message()` method.

`ics.SetRTC()`

Note: Identical to PEP8 compliant `ics.set_rtc()` method.

`ics.SetReflashDisplayCallback()`

Note: Identical to PEP8 compliant `ics.set_reflash_callback()` method.

`ics.TxMessages()`

Note: Identical to PEP8 compliant `ics.transmit_messages()` method.

`ics.ValidateHObject()`

Note: Identical to PEP8 compliant `ics.validate_hobject()` method.

`ics.base36enc(serial)`

Converts a decimal serial number to base36.

Args: serial (int): serial number.

Raises: `ics.RuntimeError`

Returns: Str: Serial Number

```
>>> ics.base36enc(device.SerialNumber)
CY0024
```

`ics.close_device(device)`

Closes the device.

Args: device (`ics.NeoDevice`): `ics.NeoDevice`

Raises: `ics.RuntimeError`

Returns: Error Count (int)

```
>>> for device in ics.find_devices():
...     ics.open_device(device)
...     # Do something with the device...
...     ics.close_device(device)
... 
```

Note: `ics.NeoDevice` will automatically close the device when it goes out of scope.

`ics.coremini_clear(device, location)`

Clears the CoreMini into the device.

Args: device (`ics.NeoDevice`): `ics.NeoDevice`

location (int): Accepts `ics.SCRIPT_LOCATION_FLASH_MEM`, `ics.SCRIPT_LOCATION_SDCARD`, or `ics.SCRIPT_LOCATION_VCAN3_MEM`

Raises: `ics.RuntimeError`

Returns: None.

```
>>> device = ics.open_device()
>>> ics.coremini_clear(device, ics.SCRIPT_LOCATION_SDCARD)
```

`ics.coremini_get_fblock_status(device, index)`

Gets the status of a Coremini Function Block at `index` on `device`.

Args: `device (ics.NeoDevice): ics.NeoDevice`

`index (int): Index of the function block.`

Raises: `ics.RuntimeError`

Returns: None on Success.

```
>>> device = ics.open_device()
>>> ics.coremini_get_fblock_status(device, 1)
True
```

`ics.coremini_get_status(device)`

Gets the status of the CoreMini in the device.

Args: `device (ics.NeoDevice): ics.NeoDevice`

Raises: `ics.RuntimeError`

Returns: True if running, otherwise False.

```
>>> device = ics.open_device()
>>> ics.coremini_get_status(device)
>>>
```

`ics.coremini_load(device, coremini, location)`

Loads the CoreMini into the device.

Args: `device (ics.NeoDevice): ics.NeoDevice`

`coremini (str/tuple): Use string to load from file, Use Tuple if file data.`

`location (int): Accepts ics.SCRIPT_LOCATION_FLASH_MEM, ics.SCRIPT_LOCATION_SDCARD, or ics.SCRIPT_LOCATION_VCAN3_MEM`

Raises: `ics.RuntimeError`

Returns: None.

```
>>> device = ics.open_device()
>>> ics.coremini_load(device, 'cmvspy.vs3cmb', ics.SCRIPT_LOCATION_SDCARD)
```

`ics.coremini_read_app_signal(device, index)`

Gets the value of a Coremini application signal at `index` on `device`.

Args: `device (ics.NeoDevice): ics.NeoDevice`

`index (int): Index of the application signal.`

Raises: `ics.RuntimeError`

Returns: int on Success.

```
>>> device = ics.open_device()
>>> ics.coremini_read_app_signal(device, 1)
52
```

`ics.coremini_read_rx_message(device, index, j1850=False)`
Gets the value of a Coremini Message at `index` on `device`.

Args: `device (ics.NeoDevice): ics.NeoDevice`

`index (int): Index of the application signal.`

`j1850 (bool): Use ics.SpyMessageJ1850 instead.`

Raises: `ics.RuntimeError`

Returns: `ics.SpyMessage Success.`

```
>>> device = ics.open_device()
>>> msg = ics.coremini_read_tx_message(device, 0)
```

`ics.coremini_read_tx_message(device, index, j1850=False)`
Gets the value of a Coremini Message at `index` on `device`.

Args: `device (ics.NeoDevice): ics.NeoDevice`

`index (int): Index of the application signal.`

`j1850 (bool): Use ics.SpyMessageJ1850 instead.`

Raises: `ics.RuntimeError`

Returns: `ics.SpyMessage Success.`

```
>>> device = ics.open_device()
>>> msg = ics.coremini_read_tx_message(device, 0)
```

`ics.coremini_start(device, location)`

Starts the CoreMini into the device.

Args: `device (ics.NeoDevice): ics.NeoDevice`

`location (int): Accepts ics.SCRIPT_LOCATION_FLASH_MEM, ics.SCRIPT_LOCATION_SDCARD, or ics.SCRIPT_LOCATION_VCAN3_MEM`

Raises: `ics.RuntimeError`

Returns: None.

```
>>> device = ics.open_device()
>>> ics.coremini_start(device, ics.SCRIPT_LOCATION_SDCARD)
```

`ics.coremini_start_fblock(device, index)`

Starts a Coremini Function Block at `index` on `device`.

Args: `device (ics.NeoDevice): ics.NeoDevice`

`index (int): Index of the function block.`

Raises: `ics.RuntimeError`

Returns: None on Success.

```
>>> device = ics.open_device()
>>> ics.coremini_start_fblock(device, 1)
```

ics.coremini_stop(device)

Stops the CoreMini into the device.

Args: device (`ics.NeoDevice`): `ics.NeoDevice`

Raises: `ics.RuntimeError`

Returns: None.

```
>>> device = ics.open_device()
>>> ics.coremini_stop(device)
```

ics.coremini_stop_fblock(device, index)

Stops a Coremini Function Block at `index` on `device`.

Args: device (`ics.NeoDevice`): `ics.NeoDevice`

index (int): Index of the function block.

Raises: `ics.RuntimeError`

Returns: None on Success.

```
>>> device = ics.open_device()
>>> ics.coremini_stop_fblock(device, 1)
```

ics.coremini_write_app_signal(device, index, value)

Sets the value of a Coremini application signal at `index` on `device`.

Args: device (`ics.NeoDevice`): `ics.NeoDevice`

index (int): Index of the application signal.

value (int): New value of the application signal.

Raises: `ics.RuntimeError`

Returns: None on Success.

```
>>> device = ics.open_device()
>>> ics.coremini_write_app_signal(device, 1, 52)
>>>
```

ics.coremini_write_rx_message(device, index, TODO)

TODO

ics.coremini_write_tx_message(device, index, msg)

TODO

ics.create_neovi_radio_message(Relay1, Relay2, Relay3, Relay4, Relay5, LED6, LED5, MSB_report_rate, LSB_report_rate, ana-log_change_report_rate, relay_timeout)

Python API only. Generates data bytes for use with neoVI RADI/O CAN Messages

Kwargs: Relay1 (boolean): Enable/Disable Relay1

Relay2 (boolean): Enable/Disable Relay2

Relay3 (boolean): Enable/Disable Relay3

Relay4 (boolean): Enable/Disable Relay4

Relay5 (boolean): Enable/Disable Relay5

LED5 (boolean): Enable/Disable LED5

LED6 (boolean): Enable/Disable LED6
MSB_report_rate (int): MSB Report Rate in ms (0-255)
LSB_report_rate (int): LSB Report Rate in ms (0-255)
analog_change_report_rate (int): Analog change report rate
relay_timeout (int): Relay Timeout (0-255)*255ms

Returns:

Tuple of data bytes for use with `ics.SpyMessage`

Raises: `ics.RuntimeError`

```
>>> msg = ics.SpyMessage()  
>>> msg.Data = ics.create_neovi_radio_message(Relay1=True, Relay4=False, _  
    ~LED6=True, MSB_report_rate=10)  
>>> msg.Data  
(65, 10, 0, 0, 0)
```

`ics.find_devices(device_type=ics.NEODEVICE_ALL)`

Args: device_type (int): Accepts ics.NEODEVICE_* Macros

stOptionsOpenNeoEx (int): Usually ics.NETID_CAN, if needed

Raises: `ics.RuntimeError`

Returns: Tuple of `ics.NeoDevice` for use in `ics.open_device()`

```
>>> for device in ics.find_devices():  
...     print(device.Name, device.SerialNumber)  
...  
neoVI FIRE 59886
```

`ics.firmware_update_required(device)`

Determines if the device firmware needs flashing.

Args: device (`ics.NeoDevice`): `ics.NeoDevice`

Raises: `ics.RuntimeError`

Returns: Boolean: True on success, False on failure.

```
>>> ics.force_firmware_update(device)  
True
```

`ics.force_firmware_update(device)`

Forces the device to flash firmware.

Args: device (`ics.NeoDevice`): `ics.NeoDevice`

Raises: `ics.RuntimeError`

Returns: Boolean: True on success, False on failure.

```
>>> ics.force_firmware_update(device)  
True
```

`ics.get_backup_power_enabled(device)`

Returns the device backup power enabled for the device.

Args: device (*ics.NeoDevice*): *ics.NeoDevice*

Raises: *ics.RuntimeError*

Returns: Boolean: True on success, False on failure.

ics.get_backup_power_ready(*device*)

Returns the device backup power is ready for the device.

Args: device (*ics.NeoDevice*): *ics.NeoDevice*

Raises: *ics.RuntimeError*

Returns: Boolean: True on success, False on failure.

ics.get_device_settings(*device*)

Gets the settings in the device.

Args: device (*ics.NeoDevice*): *ics.NeoDevice*

Raises: *ics.RuntimeError*

Returns: *ics.Vcan3Settings* or *ics.FireSettings*.

```
>>> device = ics.open_device()
>>> settings = ics.get_device_settings(device)
>>> type(settings)
<class 'ics.FireSettings'>
>>>
```

ics.get_dll_firmware_info(*device*)

Returns the DLL firmware info for the device.

Args: device (*ics.NeoDevice*): *ics.NeoDevice*

Raises: *ics.RuntimeError*

Returns: (*ics.ApiFirmwareInfo*)

```
>>> device = ics.open_device()
>>> info = ics.get_dll_firmware_info(device)
>>> info.iAppMajor
7
>>> info.iAppMinor
55
>>>
```

ics.get_dll_version(*device*)

Gets the DLL version.

Args: None

Raises: *ics.RuntimeError*

Returns: Int: DLL Version

```
>>> ics.get_dll_version()
700
```

ics.get_error_messages(*device*[, *j1850*, *timeout*])

Gets the error message(s) on the device.

Args: device (*ics.NeoDevice*): *ics.NeoDevice*

Raises: *ics.RuntimeError*

Returns: list of tuple's. :class:`tuple` contents: (error_number, description_short, description_long, severity, restart_needed)

```
>>> device = ics.open_device()
>>> errors = ics.get_error_messages(device)
```

ics.get_hw_firmware_info(device)

Returns the device firmware info for the device.

Args: device (*ics.NeoDevice*): *ics.NeoDevice*

Raises: *ics.RuntimeError*

Returns: (*ics.ApiFirmwareInfo*)

```
>>> device = ics.open_device()
>>> info = ics.get_hw_firmware_info(device)
>>> info.iAppMajor
7
>>> info.iAppMinor
55
>>>
```

ics.get_last_api_error(device)

Gets the error message from the last API call.

Args: device (*ics.NeoDevice*): *ics.NeoDevice*

Raises: *ics.RuntimeError*

Returns: Tuple: (error, description short, description long, severity, restart needed)

```
>>> device = ics.open_device()
>>> try:
...     msg = ics.coremini_read_tx_message(device, 0)
... except ics.RuntimeError as ex:
...     print(ex)
...     print(ics.get_last_api_error(device))
...
Error: coremini_read_tx_message(): icsneoScriptReadTxMessage() Failed
(224, 'Invalid Message Index for script.', 'Invalid Message Index for script.
', 16, 0)
```

ics.get_messages(device[, j1850, timeout])

Gets the message(s) on the device.

Args: device (*ics.NeoDevice*): *ics.NeoDevice*

j1850 (bool): Return *ics.SpyMessageJ1850* instead.

timeout (float): Optional timeout to wait for messages in seconds (0.1 = 100ms).

Raises: *ics.RuntimeError*

Returns: tuple of two items. First item is a tuple of *ics.SpyMessage* and second is the error count.

```
>>> device = ics.open_device()
>>> messages, errors = ics.get_messages(device)
>>> len(messages)
14
>>> hex(messages[0].ArbIDOrHeader)
```

(continues on next page)

(continued from previous page)

```
'0x160'
>>> messages[0].Data
(36, 11, 11, 177, 37, 3, 11, 199)
>>> errors
0
```

ics.get_performance_parameters(device)Gets the Performance Parameters on *device*.**Args:** device (*ics.NeoDevice*): *ics.NeoDevice***Raises:** *ics.RuntimeError***Returns:** Tuple on Success: (buffer count, buffer max, overflow count, reserved, reserved, reserved, reserved, reserved)

```
>>> device = ics.open_device()
>>> ics.get_performance_parameters(device)
(0, 24576, 0, 0, 0, 0, 0, 0)
```

ics.get_rtc(device)

Gets the Real-Time Clock of the device.

Args: device (*ics.NeoDevice*): *ics.NeoDevice***Raises:** *ics.RuntimeError***Returns:** Tuple: (datetime.datetime object, offset in seconds)

```
>>> device = ics.open_device()
>>> ics.get_rtc(device)
(datetime.datetime(2014, 9, 10, 17, 45, 45), 3)
```

ics.get_script_status()Accepts a *ics.NeoDevice*, exception on error. Returns a list of values of what ulParameters would hold**ics.get_serial_number(device)**

Gets the serial number out of the device.

Args: device (*ics.NeoDevice*): *ics.NeoDevice***Raises:** *ics.RuntimeError***Returns:** Int: Serial Number Version

```
>>> ics.get_serial_number(device)
53123
```

ics.icsneoFirmwareUpdateRequired()**Note:** Identical to PEP8 compliant *ics.firmware_update_required()* method.**ics.icsneoForceFirmwareUpdate()****Note:** Identical to PEP8 compliant *ics.force_firmware_update()* method.

`ics.icsneoGetBackupPowerEnabled()`

Note: Identical to PEP8 compliant `ics.get_backup_power_enabled()` method.

`ics.icsneoGetBackupPowerReady()`

Note: Identical to PEP8 compliant `ics.get_backup_power_ready()` method.

`ics.icsneoGetDLLFirmwareInfo()`

Note: Identical to PEP8 compliant `ics.get_dll_firmware_info()` method.

`ics.icsneoGetFireSettings()`

Note: Identical to PEP8 compliant `ics.get_device_settings()` method.

`ics.icsneoGetVCAN3Settings()`

Note: Identical to PEP8 compliant `ics.get_device_settings()` method.

`ics.icsneoLoadDefaultSettings()`

Note: Identical to PEP8 compliant `ics.load_default_settings()` method.

`ics.icsneoReadSDCard()`

Note: Identical to PEP8 compliant `ics.read_sdcards()` method.

`ics.icsneoScriptGetScriptStatusEx()`

Note: Identical to PEP8 compliant `ics.get_script_status()` method.

`ics.icsneoSetBackupPowerEnabled()`

Note: Identical to PEP8 compliant `ics.set_backup_power_enabled()` method.

`ics.icsneoSetContext()`

Note: Identical to PEP8 compliant `ics.set_context()` method.

`ics.icsneoSetFireSettings()`

Note: Identical to PEP8 compliant `ics.set_device_settings()` method.

`ics.icsneoSetVCAN3Settings()`

Note: Identical to PEP8 compliant `ics.set_device_settings()` method.

`ics.icsneoWriteSDCard()`

Note: Identical to PEP8 compliant `ics.write_sdcard()` method.

`ics.load_default_settings(device)`

Load the default settings in the device.

Args: `device (ics.NeoDevice): ics.NeoDevice`

Raises: `ics.RuntimeError`

Returns: None.

```
>>> device = ics.open_device()
>>> settings = ics.load_default_settings(device)
>>>
```

`ics.open_device(device)`

Opens the device. `device` can be omitted to return a `ics.NeoDevice` of the first free available device, a `ics.NeoDevice`, or a serial number of the device.

Args: `device (ics.NeoDevice): ics.NeoDevice`

`device (int): Serial Number of the device`

`bNetworkIDs (int): Network Enables`

`bConfigRead (int): Config Read`

`iOptions (int): DEVICE_OPTION_* defines`

`stOptionsOpenNeoEx (int): Usually ics.NETID_CAN, if needed`

Raises: `ics.RuntimeError`

Returns: If `ics.NeoDevice` is passed as a parameter, None. If serial number is passed as a parameter, a `ics.NeoDevice` will be returned. If `device` parameter is omitted, a `ics.NeoDevice` will be returned with the first available free device.

```
>>> for device in ics.find_devices():
...     ics.open_device(device)
... 
```

Note: `ics.NeoDevice` will automatically close the device when it goes out of scope.

ics.read_sdcard()

`icsneoReadSDCard()`, Accepts a `ics.NeoDevice` and sector index. Returns a bytearray of 512 bytes max. Exception on error.

ics.request_enter_sleep_mode(device, timeout_ms, mode, reserved_zero)

Signal neoVI to immediate go to sleep. Currently only supported by FIREVNET/PLASMA. If using over USB this will likely return true but never cause PLASMA to sleep since USB insertion keeps it alive. This API allows Android/Linux applications to invoke power management.

Args: `device (ics.NeoDevice): ics.NeoDevice`

`timeout_ms` (int): 16bit word for how long to wait on idle bus before going to sleep. If caller does not want to change it pass in 65535 (0xFFFF) and it will stay whatever it was set to in explorer/coremini.

`mode` (int): 16bit word for power mode to enter. If caller does not want to change it pass in 65535 (0xFFFF) and it will stay whatever it was set to in explorer/coremini. If it is zero then neoVI will do ‘normal sleep’. 0 - power mode off but calling this function will do ‘normal sleep’. 1 - normal sleep. 2 - instant sleep. 3 - comatose sleep.

`reserved_zero` (int): Reserved, Keep as zero.

Raises: `ics.RuntimeError`

Returns: Boolean: True on success, False on failure.

```
>>> ics.request_enter_sleep_mode(device, 1, 0)
True 
```

ics.set_backup_power_enabled(device, enable)

Sets the device backup power enabled for the device.

Args: `device (ics.NeoDevice): ics.NeoDevice`

Raises: `ics.RuntimeError`

Returns: Boolean: True on success, False on failure.

ics.set_context(device)

Sets the “context” of how `icsneoFindNeoDevices(Ex)` and `icsneoOpenNeoDevice(Ex)` function. If the context is 0 (null) than `icsneoFindNeoDevices(Ex)` will be system wide, searching USB and other supported computer interfaces. `icsneoFindNeoDevices` can then be used to connect to devices found in this manner. If the context is a handle to connected CAN tool than `icsneoFindNeoDevices(Ex)` will search a specific CAN bus for supported IntrepidCS CAN Nodes. Again `icsneoOpenNeoDevice(Ex)` would be used create logical connections to found CAN Nodes.

Args: `device (ics.NeoDevice): ics.NeoDevice`

Raises: `ics.RuntimeError`

Returns: Boolean: True on success, False on failure.

```
>>> ics.set_context(device)
True 
```

`ics.set_device_settings(device, settings)`

Sets the settings in the device.

Args: `device (ics.NeoDevice): ics.NeoDevice`

`settings (ics.Vcan3Settings): ics.Vcan3Settings`

or:

`settings (ics.FireSettings): ics.FireSettings`

Raises: `ics.RuntimeError`

Returns: None.

```
>>> device = ics.open_device()
>>> settings = ics.get_device_settings(device)
>>> type(settings)
<class 'ics.FireSettings'>
>>> settings.can1.Mode
0
>>> settings.can1.Mode = 3
>>> ics.set_device_settings(device, settings)
>>>
```

`ics.set_reflash_callback(callback)`

Sets the reflash display callback.

Args: `callback (function): Must be a callable Python function (def callback(msg, progress))`

Raises: `ics.RuntimeError`

Returns: None.

```
>>> def callback(msg, progress):
...     print(msg, progress)
...
>>> ics.set_reflash_callback(callback)
>>>
```

`ics.set_rtc(device[, time])`

Sets the Real-Time Clock of the device.

Args: `device (ics.NeoDevice): ics.NeoDevice`

`time (datetime.datetime): Optional. Sets to current time, if omitted.`

Raises: `ics.RuntimeError`

Returns: None.

```
>>> device = ics.open_device()
>>> ics.set_rtc(device)
```

`ics.transmit_messages(device, messages)`

Transmits message(s) on the device. `messages` can be a tuple of `ics.SpyMessage`

Args: `device (ics.NeoDevice): ics.NeoDevice`

`messages (ics.SpyMessage): ics.SpyMessage`

Raises: `ics.RuntimeError`

Returns: None.

```
>>> device = ics.open_device()
>>> msg = ics.SpyMessage()
>>> msg.ArbIDOrHeader = 0xFF
>>> msg.NetworkID = ics.NETID_HSCAN
>>> msg.Data = (0,1,2,3,4,5,6,7)
>>> ics.transmit_messages(device, msg)
>>>
```

`ics.validate_hobject(device)`

Validates the handle is valid for a `device`. Handles are only valid when the device is open.

Args: `device (ics.NeoDevice): ics.NeoDevice`

or:

`device (int): c style integer handle to the device.`

Raises: `ics.RuntimeError`

Returns: Boolean: True if valid, false otherwise.

```
>>> device = ics.open_device()
>>> ics.validate_hobject(device)
1
>>> ics.validate_hobject(device._Handle)
1
```

`ics.write_sdcard()`

`icsneoReadSDCard()`, Accepts a `ics.NeoDevice`, sector index, and a bytearray of 512 bytes. Exception on error.

CHAPTER 1

Variables

```
ics.AUTO = 0
ics.BPS100 = 5
ics.BPS1000 = 10
ics.BPS100000 = 7
ics.BPS10400 = 1
ics.BPS117647 = 8
ics.BPS125 = 6
ics.BPS20 = 0
ics.BPS2000 = 12
ics.BPS250 = 7
ics.BPS33 = 1
ics.BPS3333 = 2
ics.BPS4000 = 13
ics.BPS50 = 2
ics.BPS500 = 8
ics.BPS5000 = 0
ics.BPS50000 = 3
ics.BPS62 = 3
ics.BPS62500 = 4
ics.BPS666 = 11
ics.BPS71429 = 5
ics.BPS800 = 9
```

```
    ics.BPS83 = 4
    ics.BPS83333 = 6
    ics.BUILD_DATETIME = Jun 5 2017 23:26:17
    ics.CANFD_BRS_ENABLED = 2
    ics.CANFD_BRS_ENABLED_ISO = 4
    ics.CANFD_ENABLED = 1
    ics.CANFD_ENABLED_ISO = 3
    ics.CANFD_SETTINGS_SIZE = 10
    ics.CANTERM_SETTINGS_SIZE = 6
    ics.CAN_BPS10000 = 17
    ics.CAN_BPS5000 = 14
    ics.CAN_BPS6667 = 15
    ics.CAN_BPS8000 = 16
    ics.CAN_SETTINGS_SIZE = 12
    ics.DISABLE = 1
    ics.ETHERNET_SETTINGS_SIZE = 8
    ics.FAST_MODE = 3
    ics.GLOBAL_SETTINGS_SIZE = 908
    ics.GS_VERSION = 5
    ics.ISO15765_2_NETWORK_HSCAN = 1
    ics.ISO15765_2_NETWORK_HSCAN2 = 4
    ics.ISO15765_2_NETWORK_HSCAN3 = 8
    ics.ISO15765_2_NETWORK_HSCAN4 = 20
    ics.ISO15765_2_NETWORK_HSCAN5 = 24
    ics.ISO15765_2_NETWORK_HSCAN6 = 28
    ics.ISO15765_2_NETWORK_HSCAN7 = 32
    ics.ISO15765_2_NETWORK_MSCAN = 2
    ics.ISO15765_2_NETWORK_SWCAN = 16
    ics.ISO15765_2_NETWORK_SWCAN2 = 36
    ics.ISO9141_KEYWORD2000_SETTINGS_SIZE = 114
    ics.ISO9141_KEYWORD2000_INIT_STEP_SIZE = 6
    ics.J1708_SETTINGS_SIZE = 2
    ics.LIN_SETTINGS_SIZE = 10
    ics.LISTEN_ALL = 7
    ics.LISTEN_ONLY = 3
    ics.LOOPBACK = 2
```

```
ics.NEODEVICE_ALL = -16385
ics.NEODEVICE_ANY_ION = 1310720
ics.NEODEVICE_ANY_PLASMA = 208896
ics.NEODEVICE_BLUE = 1
ics.NEODEVICE_CT_OBD = 32768
ics.NEODEVICE_DW_VCAN = 4
ics.NEODEVICE_ECU = 128
ics.NEODEVICE_ECU15 = 4194304
ics.NEODEVICE_ECU25 = 8388608
ics.NEODEVICE_ECUCHIP_UART = 2048
ics.NEODEVICE_EEVB = 16777216
ics.NEODEVICE_FIRE = 8
ics.NEODEVICE_FIRE2 = 67108864
ics.NEODEVICE_FIRE_VNET = 8192
ics.NEODEVICE_FLEX = 134217728
ics.NEODEVICE_IEVB = 256
ics.NEODEVICE_ION_2 = 262144
ics.NEODEVICE_ION_3 = 1048576
ics.NEODEVICE_NEOANALOG = 16384
ics.NEODEVICE_NEOECUCHIP = 256
ics.NEODEVICE_OBD2_SIM = -2147483648
ics.NEODEVICE_PENDANT = 512
ics.NEODEVICE_PLASMA_1_11 = 4096
ics.NEODEVICE_PLASMA_1_12 = 65536
ics.NEODEVICE_PLASMA_1_13 = 131072
ics.NEODEVICE_RADGALAXY = 268435456
ics.NEODEVICE_RADSTAR = 524288
ics.NEODEVICE_RADSTAR2 = 536870912
ics.NEODEVICE_RED = 64
ics.NEODEVICE_SW_VCAN = 2
ics.NEODEVICE_UNKNOWN = 0
ics.NEODEVICE_VCAN3 = 16
ics.NEODEVICE_VCAN4 = 2097152
ics.NEODEVICE_VCANRF = 33554432
ics.NEODEVICE_VIRTUAL_NEOVI = 1024
ics.NEODEVICE_VIVIDCAN = 1073741824
```

```
    ics.NEOVI6_VCAN_TIMESTAMP_1 = 1e-06
    ics.NEOVI6_VCAN_TIMESTAMP_2 = 0.065536
    ics.NEOVIPRO_VCAN_TIMESTAMP_1 = 1e-06
    ics.NEOVIPRO_VCAN_TIMESTAMP_2 = 0.065536
    ics.NEOVI_3G_MAX_SETTINGS_SIZE = 908
    ics.NEOVI_COMMTYPE_FIRE_USB = 5
    ics.NEOVI_COMMTYPE_RS232 = 0
    ics.NEOVI_COMMTYPE_TCPIP = 3
    ics.NEOVI_COMMTYPE_USB_BULK = 1
    ics.NEOVI_RED_TIMESTAMP_1_10NS = 1e-08
    ics.NEOVI_RED_TIMESTAMP_1_25NS = 2.5e-08
    ics.NEOVI_RED_TIMESTAMP_2_10NS = 429.4967296
    ics.NEOVI_RED_TIMESTAMP_2_25NS = 107.3741824
    ics.NEOVI_TIMESTAMP_1 = 1.6e-06
    ics.NEOVI_TIMESTAMP_2 = 0.1048576
    ics.NEO_CFG_MPIC_HS_CAN_CNF1 = 522
    ics.NEO_CFG_MPIC_HS_CAN_CNF2 = 521
    ics.NEO_CFG_MPIC_HS_CAN_CNF3 = 520
    ics.NEO_CFG_MPIC_HS_CAN_MODE = 566
    ics.NEO_CFG_MPIC_LSFT_CAN_CNF1 = 558
    ics.NEO_CFG_MPIC_LSFT_CAN_CNF2 = 557
    ics.NEO_CFG_MPIC_LSFT_CAN_CNF3 = 556
    ics.NEO_CFG_MPIC_MS_CAN_CNF1 = 534
    ics.NEO_CFG_MPIC_MS_CAN_CNF2 = 533
    ics.NEO_CFG_MPIC_MS_CAN_CNF3 = 532
    ics.NEO_CFG_MPIC_SW_CAN_CNF1 = 546
    ics.NEO_CFG_MPIC_SW_CAN_CNF2 = 545
    ics.NEO_CFG_MPIC_SW_CAN_CNF3 = 544
    ics.NETID_3G_APP_SIGNAL_STATUS = 56
    ics.NETID_3G_FB_STATUS = 55
    ics.NETID_3G_LOGGING_OVERFLOW = 59
    ics.NETID_3G_READ_DATALINK_CM_RX_MSG = 58
    ics.NETID_3G_READ_DATALINK_CM_TX_MSG = 57
    ics.NETID_3G_READ_SETTINGS_EX = 60
    ics.NETID_3G_RESET_STATUS = 54
    ics.NETID_AUX = 7
```

```
    ics.NETID_CGI = 53
    ics.NETID_DATA_TO_HOST = 70
    ics.NETID_DEVICE = 0
    ics.NETID_ETHERNET = 93
    ics.NETID_ETHERNET_DAQ = 69
    ics.NETID_FLEXRAY = 85
    ics.NETID_FLEXRAY1A = 80
    ics.NETID_FLEXRAY1B = 81
    ics.NETID_FLEXRAY2 = 86
    ics.NETID_FLEXRAY2A = 82
    ics.NETID_FLEXRAY2B = 83
    ics.NETID_FORDSCP = 5
    ics.NETID_GMFSA = 94
    ics.NETID_HSCAN = 1
    ics.NETID_HSCAN2 = 42
    ics.NETID_HSCAN3 = 44
    ics.NETID_HSCAN4 = 61
    ics.NETID_HSCAN5 = 62
    ics.NETID_HSCAN6 = 96
    ics.NETID_HSCAN7 = 97
    ics.NETID_HW_COM_LATENCY_TEST = 512
    ics.NETID_I2C1 = 71
    ics.NETID_INVALID = 65535
    ics.NETID_ISO = 9
    ics.NETID_ISO14230 = 15
    ics.NETID_ISO2 = 14
    ics.NETID_ISO3 = 41
    ics.NETID_ISO4 = 47
    ics.NETID_ISOPIC = 10
    ics.NETID_J1708 = 6
    ics.NETID_JVPW = 8
    ics.NETID_LIN = 16
    ics.NETID_LIN2 = 48
    ics.NETID_LIN3 = 49
    ics.NETID_LIN4 = 50
    ics.NETID_LIN5 = 84
```

```
    ics.NETID_LIN6 = 98
    ics.NETID_LSFTCAN = 4
    ics.NETID_LSFTCAN2 = 99
    ics.NETID_MAIN51 = 11
    ics.NETID_MAX = 100
    ics.NETID_MOST = 51
    ics.NETID_MOST150 = 92
    ics.NETID_MOST25 = 90
    ics.NETID_MOST50 = 91
    ics.NETID_MSCAN = 2
    ics.NETID_OP_ETHERNET1 = 17
    ics.NETID_OP_ETHERNET10 = 78
    ics.NETID_OP_ETHERNET11 = 79
    ics.NETID_OP_ETHERNET12 = 87
    ics.NETID_OP_ETHERNET2 = 18
    ics.NETID_OP_ETHERNET3 = 19
    ics.NETID_OP_ETHERNET4 = 45
    ics.NETID_OP_ETHERNET5 = 46
    ics.NETID_OP_ETHERNET6 = 73
    ics.NETID_OP_ETHERNET7 = 75
    ics.NETID_OP_ETHERNET8 = 76
    ics.NETID_OP_ETHERNET9 = 77
    ics.NETID_RED = 12
    ics.NETID_RED_APP_ERROR = 52
    ics.NETID_RED_VBAT = 74
    ics.NETID_RS232 = 63
    ics.NETID_SCI = 13
    ics.NETID_SPI1 = 72
    ics.NETID_SWCAN = 3
    ics.NETID_SWCAN2 = 68
    ics.NETID_TCP = 95
    ics.NETID_TEXTAPI_TO_HOST = 71
    ics.NETID_UART = 64
    ics.NETID_UART2 = 65
    ics.NETID_UART3 = 66
    ics.NETID_UART4 = 67
```

```
    ics.NORMAL = 0
    ics.NORMAL_MODE = 2
    ics.NO_CANFD = 0
    ics.OPETH_FUNC_MEDIA CONVERTER = 1
    ics.OPETH_FUNC_TAP = 0
    ics.OPETH_FUNC_TAP_LOW_LATENCY = 2
    ics.OPETH_LINK_AUTO = 0
    ics.OPETH_LINK_MASTER = 1
    ics.OPETH_LINK_SLAVE = 2
    ics.OP_ETH_GENERAL_SETTINGS_SIZE = 20
    ics.OP_ETH_SETTINGS_SIZE = 16
    ics.PLASMA_SLAVE1_OFFSET = 100
    ics.PLASMA_SLAVE1_OFFSET_RANGE2 = 4608
    ics.PLASMA_SLAVE2_OFFSET = 200
    ics.PLASMA_SLAVE2_OFFSET_RANGE2 = 8704
    ics.PLASMA_SLAVE3_OFFSET_RANGE2 = 12800
    ics.PLASMA_SLAVE_NUM = 51
    ics.REPORT_ON_GPS = 15
    ics.REPORT_ON_KLINE = 9
    ics.REPORT_ON_LED1 = 7
    ics.REPORT_ON_LED2 = 8
    ics.REPORT_ON_MISC1 = 1
    ics.REPORT_ON_MISC2 = 2
    ics.REPORT_ON_MISC3 = 3
    ics.REPORT_ON_MISC3_AIN = 10
    ics.REPORT_ON_MISC4 = 4
    ics.REPORT_ON_MISC4_AIN = 11
    ics.REPORT_ON_MISC5 = 5
    ics.REPORT_ON_MISC5_AIN = 12
    ics.REPORT_ON_MISC6 = 6
    ics.REPORT_ON_MISC6_AIN = 13
    ics.REPORT_ON_PERIODIC = 0
    ics.REPORT_ON_PWM_IN1 = 14
    ics.RESISTOR_OFF = 1
    ics.RESISTOR_ON = 0
    ics.SCRIPT_LOCATION_FLASH_MEM = 0
```

```
    ics.SCRIPT_LOCATION_INTERNAL_FLASH = 2
    ics.SCRIPT_LOCATION_SDCARD = 1
    ics.SCRIPT_LOCATION_VCAN3_MEM = 4
    ics.SCRIPT_STATUS_RUNNING = 1
    ics.SCRIPT_STATUS_STOPPED = 0
    ics.SLEEP_MODE = 0
    ics.SLOW_MODE = 1
    ics.SPY_PROTOCOL_BEAN = 11
    ics.SPY_PROTOCOL_CAN = 1
    ics.SPY_PROTOCOL_CANFD = 30
    ics.SPY_PROTOCOL_CGI = 18
    ics.SPY_PROTOCOL_CHRYSLER_CCD = 8
    ics.SPY_PROTOCOL_CHRYSLER_JVPW = 14
    ics.SPY_PROTOCOL_CHRYSLER_SCI = 9
    ics.SPY_PROTOCOL_CUSTOM = 0
    ics.SPY_PROTOCOL_DALLAS_1WIRE = 25
    ics.SPY_PROTOCOL_ETHERNET = 29
    ics.SPY_PROTOCOL_FLEXRAY = 16
    ics.SPY_PROTOCOL_FORD_UBP = 10
    ics.SPY_PROTOCOL_GENERIC_MANCHSESTER = 26
    ics.SPY_PROTOCOL_GENERIC_UART = 22
    ics.SPY_PROTOCOL_GME_CIM_SCL_KLINE = 19
    ics.SPY_PROTOCOL_GMFSA = 31
    ics.SPY_PROTOCOL_GMLAN = 2
    ics.SPY_PROTOCOL_GM_ALDL_UART = 7
    ics.SPY_PROTOCOL_I2C = 21
    ics.SPY_PROTOCOL_ISO9141 = 5
    ics.SPY_PROTOCOL_J1708 = 13
    ics.SPY_PROTOCOL_J1850PWM = 4
    ics.SPY_PROTOCOL_J1850VPW = 3
    ics.SPY_PROTOCOL_J1939 = 15
    ics.SPY_PROTOCOL_JTAG = 23
    ics.SPY_PROTOCOL_LIN = 12
    ics.SPY_PROTOCOL_MOST = 17
    ics.SPY_PROTOCOL_SENT_PROTOCOL = 27
    ics.SPY_PROTOCOL_SPI = 20
```

```
    ics.SPY_PROTOCOL_TCP = 32
    ics.SPY_PROTOCOL_UART = 28
    ics.SPY_PROTOCOL_UNIO = 24
    ics.SPY_STATUS2_CAN_HAVE_LINK_DATA = 4194304
    ics.SPY_STATUS2_CAN_ISO15765_LOGICAL_FRAME = 2097152
    ics.SPY_STATUS2_END_OF_LONG_MESSAGE = 1048576
    ics.SPY_STATUS2_ERROR_FRAME = 131072
    ics.SPY_STATUS2_ETHERNET_CRC_ERROR = 2097152
    ics.SPY_STATUS2_ETHERNET_FCS_AVAILABLE = 8388608
    ics.SPY_STATUS2_ETHERNET_FRAME_TOO_SHORT = 4194304
    ics.SPY_STATUS2_ETHERNET_NO_PADDING = 16777216
    ics.SPY_STATUS2_ETHERNET_PREEMPTION_ENABLED = 33554432
    ics.SPY_STATUS2_FLEXRAY_NO_CRC = 33554432
    ics.SPY_STATUS2_FLEXRAY_NO_HEADERCRC = 67108864
    ics.SPY_STATUS2_FLEXRAY_TX_AB = 2097152
    ics.SPY_STATUS2_FLEXRAY_TX_AB_NO_A = 4194304
    ics.SPY_STATUS2_FLEXRAY_TX_AB_NO_B = 8388608
    ics.SPY_STATUS2_FLEXRAY_TX_AB_NO_MATCH = 16777216
    ics.SPY_STATUS2_GLOBAL_CHANGE = 65536
    ics.SPY_STATUS2_HAS_VALUE = 1
    ics.SPY_STATUS2_HIGH_VOLTAGE = 4
    ics.SPY_STATUS2_ISO_FRAME_ERROR = 134217728
    ics.SPY_STATUS2_ISO_OVERFLOW_ERROR = 268435456
    ics.SPY_STATUS2_ISO_PARITY_ERROR = 536870912
    ics.SPY_STATUS2_LIN_ERR_MSG_ID_PARITY = 67108864
    ics.SPY_STATUS2_LIN_ERR_RX_BREAK_NOT_0 = 2097152
    ics.SPY_STATUS2_LIN_ERR_RX_BREAK_TOO_SHORT = 4194304
    ics.SPY_STATUS2_LIN_ERR_RX_DATA_GREATER_8 = 16777216
    ics.SPY_STATUS2_LIN_ERR_RX_SYNC_NOT_55 = 8388608
    ics.SPY_STATUS2_LIN_ERR_TX_RX_MISMATCH = 33554432
    ics.SPY_STATUS2_LIN_ID_FRAME_ERROR = 268435456
    ics.SPY_STATUS2_LIN_NO_SLAVE_DATA = -2147483648
    ics.SPY_STATUS2_LIN_SLAVE_BYTE_ERROR = 536870912
    ics.SPY_STATUS2_LIN_SYNC_FRAME_ERROR = 134217728
    ics.SPY_STATUS2_LONG_MESSAGE = 8
    ics.SPY_STATUS2_MOST_CHANGED_PAR = -2147483648
```

```
ics.SPY_STATUS2_MOST_CONTROL_DATA = 16777216
ics.SPY_STATUS2_MOST_I2S_DUMP = 134217728
ics.SPY_STATUS2_MOST_LOW_LEVEL = 8388608
ics.SPY_STATUS2_MOST_MHP_CONTROL_DATA = 67108864
ics.SPY_STATUS2_MOST_MHP_USER_DATA = 33554432
ics.SPY_STATUS2_MOST_MOST150 = 1073741824
ics.SPY_STATUS2_MOST_MOST50 = 536870912
ics.SPY_STATUS2_MOST_PACKET_DATA = 2097152
ics.SPY_STATUS2_MOST_STATUS = 4194304
ics.SPY_STATUS2_MOST_TOO_SHORT = 268435456
ics.SPY_STATUS2_RX_TIMEOUT_ERROR = 1073741824
ics.SPY_STATUS2_VALUE_IS_BOOLEAN = 2
ics.SPY_STATUS3_CANFD_BRS = 16
ics.SPY_STATUS3_CANFD_ESI = 1
ics.SPY_STATUS3_CANFD_FDF = 8
ics.SPY_STATUS3_CANFD_IDE = 2
ics.SPY_STATUS3_CANFD_RTR = 4
ics.SPY_STATUS3_LIN_JUST_BREAK_SYNC = 1
ics.SPY_STATUS3_LIN_ONLY_UPDATE_SLAVE_TABLE_ONCE = 4
ics.SPY_STATUS3_LIN_SLAVE_DATA_TOO_SHORT = 2
ics.SPY_STATUS_ANALOG_DIGITAL_INPUT = 16777216
ics.SPY_STATUS_AUDIO_COMMENT = 4194304
ics.SPY_STATUS_AVSI_REC_OVERFLOW = 1048576
ics.SPY_STATUS_BAD_MESSAGE_BIT_TIME_ERROR = 16384
ics.SPY_STATUS_BREAK = 524288
ics.SPY_STATUS_BUS_RECOVERED = 1024
ics.SPY_STATUS_BUS_SHORTED_GND = 4096
ics.SPY_STATUS_BUS_SHORTED_PLUS = 2048
ics.SPY_STATUS_CANFD = 536870912
ics.SPY_STATUS_CAN_BUS_OFF = 512
ics.SPY_STATUS_CAN_ERROR_PASSIVE = 32
ics.SPY_STATUS_CHECKSUM_ERROR = 8192
ics.SPY_STATUS_COMM_IN_OVERFLOW = 65536
ics.SPY_STATUS_CRC_ERROR = 16
ics.SPY_STATUS_EXPECTED_LEN_MISMATCH = 131072
ics.SPY_STATUS_EXTENDED = -2147483648
```

```
ics.SPY_STATUS_FLEXRAY_PDU = 536870912
ics.SPY_STATUS_FLEXRAY_PDU_NO_UPDATE_BIT = 8
ics.SPY_STATUS_FLEXRAY_PDU_UPDATE_BIT_SET = 1073741824
ics.SPY_STATUS_GLOBAL_ERR = 1
ics.SPY_STATUS_GPS_DATA = 8388608
ics.SPY_STATUS_HEADERCRC_ERROR = 32
ics.SPY_STATUS_HIGH_SPEED = 1073741824
ics.SPY_STATUS_INCOMPLETE_FRAME = 64
ics.SPY_STATUS_INIT_MESSAGE = 536870912
ics.SPY_STATUS_LIN_MASTER = 536870912
ics.SPY_STATUS_LOST_ARBITRATION = 128
ics.SPY_STATUS_MSG_NO_MATCH = 262144
ics.SPY_STATUS_NETWORK_MESSAGE_TYPE = 67108864
ics.SPY_STATUS_REMOTE_FRAME = 8
ics.SPY_STATUS_TEST_TRIGGER = 2097152
ics.SPY_STATUS_TEXT_COMMENT = 33554432
ics.SPY_STATUS_TX_MSG = 2
ics.SPY_STATUS_TX_NOMATCH = 32768
ics.SPY_STATUS_UNDEFINED_ERROR = 256
ics.SPY_STATUS_VSI_IFR_CRC_BIT = 268435456
ics.SPY_STATUS_VSI_TX_UNDERRUN = 134217728
ics.SPY_STATUS_XTD_FRAME = 4
ics.SWCAN_AUTOSWITCH_DISABLED = 0
ics.SWCAN_AUTOSWITCH_DISABLED_RESISTOR_ENABLED = 3
ics.SWCAN_AUTOSWITCH_NO_RESISTOR = 1
ics.SWCAN_AUTOSWITCH_WITH_RESISTOR = 2
ics.SWCAN_SETTINGS_SIZE = 14
ics.UART_SETTINGS_SIZE = 16
ics.USE_TQ = 1
ics.VNETBITS_FEATURE_ANDROID_MSGS = 1
ics.VNETBITS_FEATURE_DISABLE_USB_CHECK = 2
```


CHAPTER 2

Indices and tables

- genindex
- modindex
- search

Python Module Index

i

ics, 33

Index

A

AckBytes (ics.SpyMessage attribute), 12
AckBytes (ics.SpyMessageJ1850 attribute), 13
ain_sample_period (ics.CyanSettings attribute), 3
ain_sample_period (ics.FireSettings attribute), 6
ain_sample_period (ics.RadGalaxySettings attribute), 9
ain_threshold (ics.CyanSettings attribute), 3
ain_threshold (ics.FireSettings attribute), 6
ain_threshold (ics.RadGalaxySettings attribute), 9
ApiFirmwareInfo (class in ics), 1
ArbIDOrHeader (ics.SpyMessage attribute), 12
ArgumentError, 1
AUTO (in module ics), 33
auto_baud (ics.CanSettings attribute), 3
auto_baud (ics.SWCanSettings attribute), 12
auto_neg (ics.EthernetSettings attribute), 5
AutoHandleClose (ics.NeoDevice attribute), 8

B

base36enc() (in module ics), 20
Baudrate (ics.CanSettings attribute), 2
Baudrate (ics.Iso9141Keyword2000Settings attribute), 8
Baudrate (ics.LinSettings attribute), 8
Baudrate (ics.SWCanSettings attribute), 11
Baudrate (ics.UartSettings attribute), 15
bEnReportLinkQuality (ics.OpEthGeneralSettings attribute), 9
bOptions (ics.UartSettings attribute), 15
BPS100 (in module ics), 33
BPS1000 (in module ics), 33
BPS100000 (in module ics), 33
BPS10400 (in module ics), 33
BPS117647 (in module ics), 33
BPS125 (in module ics), 33
BPS20 (in module ics), 33
BPS2000 (in module ics), 33
BPS250 (in module ics), 33
BPS33 (in module ics), 33
BPS33333 (in module ics), 33

BPS4000 (in module ics), 33
BPS50 (in module ics), 33
BPS500 (in module ics), 33
BPS5000 (in module ics), 33
BPS50000 (in module ics), 33
BPS62 (in module ics), 33
BPS62500 (in module ics), 33
BPS666 (in module ics), 33
BPS71429 (in module ics), 33
BPS800 (in module ics), 33
BPS83 (in module ics), 33
BPS83333 (in module ics), 34
brgh (ics.Iso9141Keyword2000Settings attribute), 8
brgh (ics.LinSettings attribute), 8
brgh (ics.UartSettings attribute), 15
BRP (ics.CanSettings attribute), 2
BRP (ics.SWCanSettings attribute), 11
bTapEnPtp (ics.OpEthGeneralSettings attribute), 9
bTapEnSwitch (ics.OpEthGeneralSettings attribute), 9
BUILD_DATETIME (in module ics), 34

C

can1 (ics.CyanSettings attribute), 3
can1 (ics.FireSettings attribute), 6
can1 (ics.RadGalaxySettings attribute), 9
can1 (ics.Vcan3Settings attribute), 15
can1 (ics.VcanRFSettings attribute), 15
can1_options (ics.TextApiSettings attribute), 14
can1_rx_id (ics.TextApiSettings attribute), 14
can1_tx_id (ics.TextApiSettings attribute), 14
can2 (ics.CyanSettings attribute), 3
can2 (ics.FireSettings attribute), 6
can2 (ics.RadGalaxySettings attribute), 9
can2 (ics.Vcan3Settings attribute), 15
can2 (ics.VcanRFSettings attribute), 16
can2_options (ics.TextApiSettings attribute), 14
can2_rx_id (ics.TextApiSettings attribute), 14
can2_tx_id (ics.TextApiSettings attribute), 14
can3 (ics.CyanSettings attribute), 3
can3 (ics.FireSettings attribute), 6

can3 (ics.RadGalaxySettings attribute), 9
can3 (ics.VcanRFSettings attribute), 16
can3_options (ics.TextApiSettings attribute), 14
can3_rx_id (ics.TextApiSettings attribute), 14
can3_tx_id (ics.TextApiSettings attribute), 14
can4 (ics.CyanSettings attribute), 3
can4 (ics.FireSettings attribute), 6
can4 (ics.RadGalaxySettings attribute), 9
can4 (ics.VcanRFSettings attribute), 16
can4_options (ics.TextApiSettings attribute), 15
can4_rx_id (ics.TextApiSettings attribute), 15
can4_tx_id (ics.TextApiSettings attribute), 15
can5 (ics.CyanSettings attribute), 3
can5 (ics.RadGalaxySettings attribute), 9
can6 (ics.CyanSettings attribute), 3
can6 (ics.RadGalaxySettings attribute), 9
can7 (ics.CyanSettings attribute), 3
can7 (ics.RadGalaxySettings attribute), 9
can8 (ics.CyanSettings attribute), 3
can8 (ics.RadGalaxySettings attribute), 9
CAN_BPS10000 (in module ics), 34
CAN_BPS5000 (in module ics), 34
CAN_BPS6667 (in module ics), 34
CAN_BPS8000 (in module ics), 34
CAN_SETTINGS_SIZE (in module ics), 34
can_switch_mode (ics.CyanSettings attribute), 3
can_switch_mode (ics.RadGalaxySettings attribute), 10
canfd1 (ics.CyanSettings attribute), 3
canfd1 (ics.RadGalaxySettings attribute), 10
canfd2 (ics.CyanSettings attribute), 3
canfd2 (ics.RadGalaxySettings attribute), 10
canfd3 (ics.CyanSettings attribute), 3
canfd3 (ics.RadGalaxySettings attribute), 10
canfd4 (ics.CyanSettings attribute), 3
canfd4 (ics.RadGalaxySettings attribute), 10
canfd5 (ics.CyanSettings attribute), 3
canfd5 (ics.RadGalaxySettings attribute), 10
canfd6 (ics.CyanSettings attribute), 3
canfd6 (ics.RadGalaxySettings attribute), 10
canfd7 (ics.CyanSettings attribute), 3
canfd7 (ics.RadGalaxySettings attribute), 10
canfd8 (ics.CyanSettings attribute), 4
canfd8 (ics.RadGalaxySettings attribute), 10
CANFD_BRS_ENABLED (in module ics), 34
CANFD_BRS_ENABLED_ISO (in module ics), 34
CANFD_ENABLED (in module ics), 34
CANFD_ENABLED_ISO (in module ics), 34
CANFD_SETTINGS_SIZE (in module ics), 34
CanFdSettings (class in ics), 2
CanSettings (class in ics), 2
CANTERM_SETTINGS_SIZE (in module ics), 34
cgi_baud (ics.FireSettings attribute), 6
cgi_chksum_enable (ics.FireSettings attribute), 6
cgi_enable_reserved (ics.FireSettings attribute), 6

cgi_rx_ifs_bit_times (ics.FireSettings attribute), 6
cgi_tx_ifs_bit_times (ics.FireSettings attribute), 6
chksum_enabled (ics.Iso9141Keyword2000Settings attribute), 8
close_device() (in module ics), 20
ClosePort() (in module ics), 17
coremini_clear() (in module ics), 20
coremini_get_fblock_status() (in module ics), 21
coremini_get_status() (in module ics), 21
coremini_load() (in module ics), 21
coremini_read_app_signal() (in module ics), 21
coremini_read_rx_message() (in module ics), 22
coremini_read_tx_message() (in module ics), 22
coremini_start() (in module ics), 22
coremini_start_fblock() (in module ics), 22
coremini_stop() (in module ics), 22
coremini_stop_fblock() (in module ics), 23
coremini_write_app_signal() (in module ics), 23
coremini_write_rx_message() (in module ics), 23
coremini_write_tx_message() (in module ics), 23
create_neovi_radio_message() (in module ics), 23
CyanSettings (class in ics), 3

D

Data (ics.SpyMessage attribute), 12
Data (ics.SpyMessageJ1850 attribute), 13
DescriptionID (ics.SpyMessage attribute), 12
DescriptionID (ics.SpyMessageJ1850 attribute), 13
DeviceType (ics.NeoDevice attribute), 8
digitalIoThresholdEnable (ics.CyanSettings attribute), 4
digitalIoThresholdTicks (ics.CyanSettings attribute), 4
DISABLE (in module ics), 34
disableUsbCheckOnBoot (ics.CyanSettings attribute), 4
duplex (ics.EthernetSettings attribute), 5

E

enableLatencyTest (ics.CyanSettings attribute), 4
ethernet (ics.CyanSettings attribute), 4
ETHERNET_SETTINGS_SIZE (in module ics), 34
EthernetSettings (class in ics), 5
ExtraDataPtr (ics.SpyMessage attribute), 12
ExtraDataPtr (ics.SpyMessageJ1850 attribute), 13
ExtraDataPtrEnabled (ics.SpyMessage attribute), 12
ExtraDataPtrEnabled (ics.SpyMessageJ1850 attribute), 13

F

fast_init_network_enables_1 (ics.FireSettings attribute), 6
fast_init_network_enables_2 (ics.FireSettings attribute), 6
FAST_MODE (in module ics), 34
FDBaudrate (ics.CanFdSettings attribute), 2
FDBRP (ics.CanFdSettings attribute), 2

FDFMode (ics.CanFdSettings attribute), 2
 FDTqProp (ics.CanFdSettings attribute), 2
 FDTqSeg1 (ics.CanFdSettings attribute), 2
 FDTqSeg2 (ics.CanFdSettings attribute), 2
 FDTqSync (ics.CanFdSettings attribute), 2
 find_devices() (in module ics), 24
 FindNeoDevices() (in module ics), 17
 FireSettings (class in ics), 6
 firmware_update_required() (in module ics), 24
 flow_control (ics.UartSettings attribute), 15
 force_firmware_update() (in module ics), 24

G

get_backup_power_enabled() (in module ics), 24
 get_backup_power_ready() (in module ics), 25
 get_device_settings() (in module ics), 25
 get_dll_firmware_info() (in module ics), 25
 get_dll_version() (in module ics), 25
 get_error_messages() (in module ics), 25
 get_hw_firmware_info() (in module ics), 26
 get_last_api_error() (in module ics), 26
 get_messages() (in module ics), 26
 get_performance_parameters() (in module ics), 27
 get_rtc() (in module ics), 27
 get_script_status() (in module ics), 27
 get_serial_number() (in module ics), 27
 GetDLLVersion() (in module ics), 17
 GetErrorMessages() (in module ics), 17
 GetHWFirmwareInfo() (in module ics), 17
 GetLastAPIError() (in module ics), 17
 GetMessages() (in module ics), 17
 GetPerformanceParameters() (in module ics), 17
 GetRTC() (in module ics), 17
 GetSerialNumber() (in module ics), 18
 GLOBAL_SETTINGS_SIZE (in module ics), 34
 GS_VERSION (in module ics), 34

H

Handle (ics.NeoDevice attribute), 8
 Header (ics.SpyMessageJ1850 attribute), 13
 high_speed_auto_switch (ics.SWCanSettings attribute), 12

I

iAppMajor (ics.ApiFirmwareInfo attribute), 1
 iAppMinor (ics.ApiFirmwareInfo attribute), 1
 iBoardRevMajor (ics.ApiFirmwareInfo attribute), 1
 iBoardRevMinor (ics.ApiFirmwareInfo attribute), 1
 iBootLoaderVersionMajor (ics.ApiFirmwareInfo attribute), 1
 iBootLoaderVersionMinor (ics.ApiFirmwareInfo attribute), 1
 ics (module), 1
 icsneoFirmwareUpdateRequired() (in module ics), 27

icsneoForceFirmwareUpdate() (in module ics), 27
 icsneoGetBackupPowerEnabled() (in module ics), 27
 icsneoGetBackupPowerReady() (in module ics), 28
 icsneoGetDLLFirmwareInfo() (in module ics), 28
 icsneoGetFireSettings() (in module ics), 28
 icsneoGetVCAN3Settings() (in module ics), 28
 icsneoLoadDefaultSettings() (in module ics), 28
 icsneoReadSDCard() (in module ics), 28
 icsneoScriptGetScriptStatusEx() (in module ics), 28
 icsneoSetBackupPowerEnabled() (in module ics), 28
 icsneoSetContext() (in module ics), 28
 icsneoSetFireSettings() (in module ics), 29
 icsneoSetVCAN3Settings() (in module ics), 29
 icsneoWriteSDCard() (in module ics), 29
 idle_wakeup_network_enables_1 (ics.RadGalaxySettings attribute), 10
 idle_wakeup_network_enables_1 (ics.VcanRFSettings attribute), 16
 idle_wakeup_network_enables_2 (ics.RadGalaxySettings attribute), 10
 idle_wakeup_network_enables_2 (ics.VcanRFSettings attribute), 16
 idle_wakeup_network_enables_3 (ics.CyanSettings attribute), 4
 idle_wakeup_network_enables_3 (ics.RadGalaxySettings attribute), 10
 iMainFirmChkSum (ics.ApiFirmwareInfo attribute), 1
 iMainFirmDateDay (ics.ApiFirmwareInfo attribute), 1
 iMainFirmDateHour (ics.ApiFirmwareInfo attribute), 1
 iMainFirmDateMin (ics.ApiFirmwareInfo attribute), 1
 iMainFirmDateMonth (ics.ApiFirmwareInfo attribute), 2
 iMainFirmDateSecond (ics.ApiFirmwareInfo attribute), 2
 iMainFirmDateYear (ics.ApiFirmwareInfo attribute), 2
 iMainVnetHWrevMajor (ics.ApiFirmwareInfo attribute), 2
 iMainVnetHWrevMinor (ics.ApiFirmwareInfo attribute), 2
 iMainVnetSRAMSize (ics.ApiFirmwareInfo attribute), 2
 iManufactureDay (ics.ApiFirmwareInfo attribute), 2
 iManufactureMonth (ics.ApiFirmwareInfo attribute), 2
 iManufactureYear (ics.ApiFirmwareInfo attribute), 2
 init_steps (ics.Iso9141Keyword2000Settings attribute), 8
 innerFrameDelay25us (ics.CanSettings attribute), 3
 ISO15765_2_NETWORK_HSCAN (in module ics), 34
 ISO15765_2_NETWORK_HSCAN2 (in module ics), 34
 ISO15765_2_NETWORK_HSCAN3 (in module ics), 34
 ISO15765_2_NETWORK_HSCAN4 (in module ics), 34
 ISO15765_2_NETWORK_HSCAN5 (in module ics), 34
 ISO15765_2_NETWORK_HSCAN6 (in module ics), 34
 ISO15765_2_NETWORK_HSCAN7 (in module ics), 34
 ISO15765_2_NETWORK_MSCAN (in module ics), 34
 ISO15765_2_NETWORK_SWCAN (in module ics), 34
 ISO15765_2_NETWORK_SWCAN2 (in module ics), 34

iso15765_separation_time_offset (ics.CyanSettings attribute), 4
iso15765_separation_time_offset (ics.FireSettings attribute), 6
iso15765_separation_time_offset (ics.RadGalaxySettings attribute), 10
iso15765_separation_time_offset (ics.Vcan3Settings attribute), 15
iso15765_separation_time_offset (ics.VcanRFSettings attribute), 16
ISO9141_KEYWORD2000_INIT_STEP_SIZE (in module ics), 34
ISO9141_KEYWORD2000_SETTINGS_SIZE (in module ics), 34
iso9141_kwp_enable_reserved (ics.FireSettings attribute), 6
iso9141_kwp_enable_reserved (ics.VcanRFSettings attribute), 16
iso9141_kwp_settings (ics.FireSettings attribute), 6
iso9141_kwp_settings (ics.VcanRFSettings attribute), 16
iso9141_kwp_settings_1 (ics.CyanSettings attribute), 4
iso9141_kwp_settings_1 (ics.RadGalaxySettings attribute), 10
iso9141_kwp_settings_2 (ics.CyanSettings attribute), 4
iso9141_kwp_settings_2 (ics.FireSettings attribute), 6
iso9141_kwp_settings_2 (ics.VcanRFSettings attribute), 16
iso9141_kwp_settings_3 (ics.CyanSettings attribute), 4
iso9141_kwp_settings_3 (ics.FireSettings attribute), 6
iso9141_kwp_settings_4 (ics.CyanSettings attribute), 4
iso9141_kwp_settings_4 (ics.FireSettings attribute), 6
Iso9141Keyword2000InitSteps (class in ics), 7
Iso9141Keyword2000Settings (class in ics), 8
iso_msg_termination (ics.FireSettings attribute), 6
iso_msg_termination (ics.VcanRFSettings attribute), 16
iso_msg_termination_1 (ics.CyanSettings attribute), 4
iso_msg_termination_1 (ics.RadGalaxySettings attribute), 10
iso_msg_termination_2 (ics.CyanSettings attribute), 4
iso_msg_termination_2 (ics.FireSettings attribute), 6
iso_msg_termination_2 (ics.VcanRFSettings attribute), 16
iso_msg_termination_3 (ics.CyanSettings attribute), 4
iso_msg_termination_3 (ics.FireSettings attribute), 6
iso_msg_termination_4 (ics.CyanSettings attribute), 4
iso_msg_termination_4 (ics.FireSettings attribute), 6
iso_parity (ics.FireSettings attribute), 6
iso_parity (ics.VcanRFSettings attribute), 16
iso_parity_1 (ics.CyanSettings attribute), 4
iso_parity_1 (ics.RadGalaxySettings attribute), 10
iso_parity_2 (ics.CyanSettings attribute), 4
iso_parity_2 (ics.FireSettings attribute), 6
iso_parity_2 (ics.VcanRFSettings attribute), 16
iso_parity_3 (ics.CyanSettings attribute), 4
iso_parity_3 (ics.FireSettings attribute), 7
iso_parity_4 (ics.CyanSettings attribute), 4
iso_parity_4 (ics.FireSettings attribute), 7
iso_tester_pullup_enable (ics.FireSettings attribute), 7
iso_tester_pullup_enable (ics.VcanRFSettings attribute), 16
IsOpen (ics.NeoDevice attribute), 8
iTType (ics.ApiFirmwareInfo attribute), 2

J

J1708_SETTINGS_SIZE (in module ics), 34

K

k (ics.Iso9141Keyword2000InitSteps attribute), 7

L

l (ics.Iso9141Keyword2000InitSteps attribute), 8
led_mode (ics.EthernetSettings attribute), 5
lin1 (ics.CyanSettings attribute), 4
lin1 (ics.FireSettings attribute), 7
lin1 (ics.RadGalaxySettings attribute), 10
lin1 (ics.VcanRFSettings attribute), 16
lin2 (ics.CyanSettings attribute), 4
lin2 (ics.FireSettings attribute), 7
lin2 (ics.VcanRFSettings attribute), 16
lin3 (ics.CyanSettings attribute), 4
lin3 (ics.FireSettings attribute), 7
lin4 (ics.CyanSettings attribute), 4
lin4 (ics.FireSettings attribute), 7
lin5 (ics.CyanSettings attribute), 5
lin6 (ics.CyanSettings attribute), 5
LIN_SETTINGS_SIZE (in module ics), 34
link_speed (ics.EthernetSettings attribute), 5
LinSettings (class in ics), 8
LISTEN_ALL (in module ics), 34
LISTEN_ONLY (in module ics), 34
load_default_settings() (in module ics), 29
LOOPBACK (in module ics), 34
lsft (ics.FireSettings attribute), 7
lsft1 (ics.CyanSettings attribute), 5
lsft2 (ics.CyanSettings attribute), 5

M

MasterResistor (ics.LinSettings attribute), 8
MaxAllowedClients (ics.NeoDevice attribute), 8
MessagePieceID (ics.SpyMessage attribute), 12
MessagePieceID (ics.SpyMessageJ1850 attribute), 13
misc_io_analog_enable (ics.CyanSettings attribute), 5
misc_io_analog_enable (ics.FireSettings attribute), 7
misc_io_analog_enable (ics.RadGalaxySettings attribute), 10
misc_io_analog_enable (ics.VcanRFSettings attribute), 16

misc_io_initial_ddr (ics.CyanSettings attribute), 5
 misc_io_initial_ddr (ics.FireSettings attribute), 7
 misc_io_initial_ddr (ics.RadGalaxySettings attribute), 10
 misc_io_initial_ddr (ics.Vcan3Settings attribute), 15
 misc_io_initial_ddr (ics.VcanRFSettings attribute), 16
 misc_io_initial_latch (ics.CyanSettings attribute), 5
 misc_io_initial_latch (ics.FireSettings attribute), 7
 misc_io_initial_latch (ics.RadGalaxySettings attribute), 10
 misc_io_initial_latch (ics.Vcan3Settings attribute), 15
 misc_io_initial_latch (ics.VcanRFSettings attribute), 16
 misc_io_on_report_events (ics.CyanSettings attribute), 5
 misc_io_on_report_events (ics.FireSettings attribute), 7
 misc_io_on_report_events (ics.RadGalaxySettings attribute), 10
 misc_io_on_report_events (ics.Vcan3Settings attribute), 15
 misc_io_on_report_events (ics.VcanRFSettings attribute), 16
 misc_io_report_period (ics.CyanSettings attribute), 5
 misc_io_report_period (ics.FireSettings attribute), 7
 misc_io_report_period (ics.RadGalaxySettings attribute), 10
 misc_io_report_period (ics.Vcan3Settings attribute), 15
 misc_io_report_period (ics.VcanRFSettings attribute), 16
 MiscData (ics.SpyMessage attribute), 12
 MiscData (ics.SpyMessageJ1850 attribute), 13
 Mode (ics.CanSettings attribute), 2
 Mode (ics.LinSettings attribute), 8
 Mode (ics.SWCanSettings attribute), 11

N

Name (ics.NeoDevice attribute), 8
 NEO_CFG_MPIC_HS_CAN_CNF1 (in module ics), 36
 NEO_CFG_MPIC_HS_CAN_CNF2 (in module ics), 36
 NEO_CFG_MPIC_HS_CAN_CNF3 (in module ics), 36
 NEO_CFG_MPIC_HS_CAN_MODE (in module ics), 36
 NEO_CFG_MPIC_LSFT_CAN_CNF1 (in module ics), 36
 NEO_CFG_MPIC_LSFT_CAN_CNF2 (in module ics), 36
 NEO_CFG_MPIC_LSFT_CAN_CNF3 (in module ics), 36
 NEO_CFG_MPIC_MS_CAN_CNF1 (in module ics), 36
 NEO_CFG_MPIC_MS_CAN_CNF2 (in module ics), 36
 NEO_CFG_MPIC_MS_CAN_CNF3 (in module ics), 36
 NEO_CFG_MPIC_SW_CAN_CNF1 (in module ics), 36
 NEO_CFG_MPIC_SW_CAN_CNF2 (in module ics), 36
 NEO_CFG_MPIC_SW_CAN_CNF3 (in module ics), 36
 NeoDevice (class in ics), 8
 NEODEVICE_ALL (in module ics), 34
 NEODEVICE_ANY_ION (in module ics), 35
 NEODEVICE_ANY_PLASMA (in module ics), 35
 NEODEVICE_BLUE (in module ics), 35
 NEODEVICE_CT_OBD (in module ics), 35
 NEODEVICE_DW_VCAN (in module ics), 35
 NEODEVICE_ECU (in module ics), 35
 NEODEVICE_ECU15 (in module ics), 35
 NEODEVICE_ECU25 (in module ics), 35
 NEODEVICE_ECUCHIP_UART (in module ics), 35
 NEODEVICE_EEVB (in module ics), 35
 NEODEVICE_FIRE (in module ics), 35
 NEODEVICE_FIRE2 (in module ics), 35
 NEODEVICE_FIRE_VNET (in module ics), 35
 NEODEVICE_FLEX (in module ics), 35
 NEODEVICE_IEVB (in module ics), 35
 NEODEVICE_ION_2 (in module ics), 35
 NEODEVICE_ION_3 (in module ics), 35
 NEODEVICE_NEOANALOG (in module ics), 35
 NEODEVICE_NEOECUCHIP (in module ics), 35
 NEODEVICE_OBD2_SIM (in module ics), 35
 NEODEVICE_PENDANT (in module ics), 35
 NEODEVICE_PLASMA_1_11 (in module ics), 35
 NEODEVICE_PLASMA_1_12 (in module ics), 35
 NEODEVICE_PLASMA_1_13 (in module ics), 35
 NEODEVICE_RADGALAXY (in module ics), 35
 NEODEVICE_RADSTAR (in module ics), 35
 NEODEVICE_RADSTAR2 (in module ics), 35
 NEODEVICE_RED (in module ics), 35
 NEODEVICE_SW_VCAN (in module ics), 35
 NEODEVICE_UNKNOWN (in module ics), 35
 NEODEVICE_VCAN3 (in module ics), 35
 NEODEVICE_VCAN4 (in module ics), 35
 NEODEVICE_VCANRF (in module ics), 35
 NEODEVICE_VIRTUAL_NEOVI (in module ics), 35
 NEODEVICE_VIVIDCAN (in module ics), 35
 NEOVI6_VCAN_TIMESTAMP_1 (in module ics), 35
 NEOVI6_VCAN_TIMESTAMP_2 (in module ics), 36
 NEOVI_3G_MAX_SETTINGS_SIZE (in module ics), 36
 NEOVI_COMMTYPE_FIRE_USB (in module ics), 36
 NEOVI_COMMTYPE_RS232 (in module ics), 36
 NEOVI_COMMTYPE_TCPIP (in module ics), 36
 NEOVI_COMMTYPE_USB_BULK (in module ics), 36
 NEOVI_RED_TIMESTAMP_1_10NS (in module ics), 36
 NEOVI_RED_TIMESTAMP_1_25NS (in module ics), 36
 NEOVI_RED_TIMESTAMP_2_10NS (in module ics), 36
 NEOVI_RED_TIMESTAMP_2_25NS (in module ics), 36
 NEOVI_TIMESTAMP_1 (in module ics), 36
 NEOVI_TIMESTAMP_2 (in module ics), 36
 NEOVIPRO_VCAN_TIMESTAMP_1 (in module ics), 36
 NEOVIPRO_VCAN_TIMESTAMP_2 (in module ics), 36

NETID_3G_APP_SIGNAL_STATUS (in module `ics`), 36
NETID_3G_FB_STATUS (in module `ics`), 36
NETID_3G_LOGGING_OVERFLOW (in module `ics`), 36
NETID_3G_READ_DATALINK_CM_RX_MSG (in module `ics`), 36
NETID_3G_READ_DATALINK_CM_TX_MSG (in module `ics`), 36
NETID_3G_READ_SETTINGS_EX (in module `ics`), 36
NETID_3G_RESET_STATUS (in module `ics`), 36
NETID_AUX (in module `ics`), 36
NETID_CGI (in module `ics`), 36
NETID_DATA_TO_HOST (in module `ics`), 37
NETID_DEVICE (in module `ics`), 37
NETID_ETHERNET (in module `ics`), 37
NETID_ETHERNET_DAQ (in module `ics`), 37
NETID_FLEXRAY (in module `ics`), 37
NETID_FLEXRAY1A (in module `ics`), 37
NETID_FLEXRAY1B (in module `ics`), 37
NETID_FLEXRAY2 (in module `ics`), 37
NETID_FLEXRAY2A (in module `ics`), 37
NETID_FLEXRAY2B (in module `ics`), 37
NETID_FORDSCP (in module `ics`), 37
NETID_GMFSA (in module `ics`), 37
NETID_HSCAN (in module `ics`), 37
NETID_HSCAN2 (in module `ics`), 37
NETID_HSCAN3 (in module `ics`), 37
NETID_HSCAN4 (in module `ics`), 37
NETID_HSCAN5 (in module `ics`), 37
NETID_HSCAN6 (in module `ics`), 37
NETID_HSCAN7 (in module `ics`), 37
NETID_HW_COM_LATENCY_TEST (in module `ics`), 37
NETID_I2C1 (in module `ics`), 37
NETID_INVALID (in module `ics`), 37
NETID_ISO (in module `ics`), 37
NETID_ISO14230 (in module `ics`), 37
NETID_ISO2 (in module `ics`), 37
NETID_ISO3 (in module `ics`), 37
NETID_ISO4 (in module `ics`), 37
NETID_ISOPIC (in module `ics`), 37
NETID_J1708 (in module `ics`), 37
NETID_JVPW (in module `ics`), 37
NETID_LIN (in module `ics`), 37
NETID_LIN2 (in module `ics`), 37
NETID_LIN3 (in module `ics`), 37
NETID_LIN4 (in module `ics`), 37
NETID_LIN5 (in module `ics`), 37
NETID_LIN6 (in module `ics`), 37
NETID_LSFTCAN (in module `ics`), 38
NETID_LSFTCAN2 (in module `ics`), 38
NETID_MAIN51 (in module `ics`), 38
NETID_MAX (in module `ics`), 38
NETID_MOST (in module `ics`), 38
NETID_MOST150 (in module `ics`), 38
NETID_MOST25 (in module `ics`), 38
NETID_MOST50 (in module `ics`), 38
NETID_MSCAN (in module `ics`), 38
NETID_OP_ETHERNET1 (in module `ics`), 38
NETID_OP_ETHERNET10 (in module `ics`), 38
NETID_OP_ETHERNET11 (in module `ics`), 38
NETID_OP_ETHERNET12 (in module `ics`), 38
NETID_OP_ETHERNET2 (in module `ics`), 38
NETID_OP_ETHERNET3 (in module `ics`), 38
NETID_OP_ETHERNET4 (in module `ics`), 38
NETID_OP_ETHERNET5 (in module `ics`), 38
NETID_OP_ETHERNET6 (in module `ics`), 38
NETID_OP_ETHERNET7 (in module `ics`), 38
NETID_OP_ETHERNET8 (in module `ics`), 38
NETID_OP_ETHERNET9 (in module `ics`), 38
NETID_RED (in module `ics`), 38
NETID_RED_APP_ERROR (in module `ics`), 38
NETID_RED_VBAT (in module `ics`), 38
NETID_RS232 (in module `ics`), 38
NETID_SCI (in module `ics`), 38
NETID_SPI1 (in module `ics`), 38
NETID_SWCAN (in module `ics`), 38
NETID_SWCAN2 (in module `ics`), 38
NETID_TCP (in module `ics`), 38
NETID_TEXTAPI_TO_HOST (in module `ics`), 38
NETID_UART (in module `ics`), 38
NETID_UART2 (in module `ics`), 38
NETID_UART3 (in module `ics`), 38
NETID_UART4 (in module `ics`), 38
network_enabled_on_boot (`ics.CyanSettings` attribute), 5
network_enabled_on_boot (`ics.FireSettings` attribute), 7
network_enabled_on_boot (`ics.RadGalaxySettings` attribute), 10
network_enabled_on_boot (`ics.Vcan3Settings` attribute), 15
network_enabled_on_boot (`ics.VcanRFSettings` attribute), 16
network_enables (`ics.CyanSettings` attribute), 5
network_enables (`ics.FireSettings` attribute), 7
network_enables (`ics.RadGalaxySettings` attribute), 10
network_enables (`ics.TextApiSettings` attribute), 15
network_enables (`ics.Vcan3Settings` attribute), 15
network_enables (`ics.VcanRFSettings` attribute), 16
network_enables_2 (`ics.CyanSettings` attribute), 5
network_enables_2 (`ics.FireSettings` attribute), 7
network_enables_2 (`ics.RadGalaxySettings` attribute), 10
network_enables_2 (`ics.VcanRFSettings` attribute), 16
network_enables_3 (`ics.CyanSettings` attribute), 5
network_enables_3 (`ics.RadGalaxySettings` attribute), 10
NetworkID (`ics.SpyMessage` attribute), 12
NetworkID (`ics.SpyMessageJ1850` attribute), 13
NO_CANFD (in module `ics`), 39
NodeID (`ics.SpyMessage` attribute), 12

NodeID (ics.SpyMessageJ1850 attribute), 13
noExtraDataPtrCleanup (ics.SpyMessage attribute), 13
noExtraDataPtrCleanup (ics.SpyMessageJ1850 attribute), 14

NORMAL (in module ics), 38
NORMAL_MODE (in module ics), 39
NumberBytesData (ics.SpyMessage attribute), 12
NumberBytesData (ics.SpyMessageJ1850 attribute), 13
NumberBytesHeader (ics.SpyMessage attribute), 12
NumberBytesHeader (ics.SpyMessageJ1850 attribute), 14
NumberOfClients (ics.NeoDevice attribute), 8

O

OP_ETH_GENERAL_SETTINGS_SIZE (in module ics), 39
OP_ETH_SETTINGS_SIZE (in module ics), 39
open_device() (in module ics), 29
OpenNeoDevice() (in module ics), 18
opEth1 (ics.RadGalaxySettings attribute), 10
opEth10 (ics.RadGalaxySettings attribute), 11
opEth11 (ics.RadGalaxySettings attribute), 11
opEth12 (ics.RadGalaxySettings attribute), 11
opEth2 (ics.RadGalaxySettings attribute), 11
opEth3 (ics.RadGalaxySettings attribute), 11
opEth4 (ics.RadGalaxySettings attribute), 11
opEth5 (ics.RadGalaxySettings attribute), 11
opEth6 (ics.RadGalaxySettings attribute), 11
opEth7 (ics.RadGalaxySettings attribute), 11
opEth8 (ics.RadGalaxySettings attribute), 11
opEth9 (ics.RadGalaxySettings attribute), 11
OPETH_FUNC_MEDIACONVERTER (in module ics), 39
OPETH_FUNC_TAP (in module ics), 39
OPETH_FUNC_TAP_LOW_LATENCY (in module ics), 39
OPETH_LINK_AUTO (in module ics), 39
OPETH_LINK_MASTER (in module ics), 39
OPETH_LINK_SLAVE (in module ics), 39
opEthGen (ics.RadGalaxySettings attribute), 11
OpEthGeneralSettings (class in ics), 8
OpEthSettings (class in ics), 9

P

p2_500us (ics.Iso9141Keyword2000Settings attribute), 8
p3_500us (ics.Iso9141Keyword2000Settings attribute), 8
p4_500us (ics.Iso9141Keyword2000Settings attribute), 8
parity (ics.UartSettings attribute), 15
perf_en (ics.CyanSettings attribute), 5
perf_en (ics.FireSettings attribute), 7
perf_en (ics.RadGalaxySettings attribute), 11
perf_en (ics.Vcan3Settings attribute), 15
perf_en (ics.VcanRFSettings attribute), 16
PLASMA_SLAVE1_OFFSET_RANGE2 (in module ics), 39

PLASMA_SLAVE1_OFFSET_RANGE2 (in module ics), 39
PLASMA_SLAVE2_OFFSET (in module ics), 39
PLASMA_SLAVE2_OFFSET_RANGE2 (in module ics), 39
PLASMA_SLAVE3_OFFSET_RANGE2 (in module ics), 39
PLASMA_SLAVE_NUM (in module ics), 39
preemption_en (ics.OpEthSettings attribute), 9
Protocol (ics.SpyMessage attribute), 12
Protocol (ics.SpyMessageJ1850 attribute), 14
pwm_man_timeout (ics.FireSettings attribute), 7
pwr_man_enable (ics.CyanSettings attribute), 5
pwr_man_enable (ics.FireSettings attribute), 7
pwr_man_enable (ics.RadGalaxySettings attribute), 11
pwr_man_enable (ics.VcanRFSettings attribute), 16
pwr_man_timeout (ics.CyanSettings attribute), 5
pwr_man_timeout (ics.RadGalaxySettings attribute), 11
pwr_man_timeout (ics.VcanRFSettings attribute), 16

R

RadGalaxySettings (class in ics), 9
read_sdcard() (in module ics), 30
REPORT_ON_GPS (in module ics), 39
REPORT_ON_KLINE (in module ics), 39
REPORT_ON_LED1 (in module ics), 39
REPORT_ON_LED2 (in module ics), 39
REPORT_ON_MISC1 (in module ics), 39
REPORT_ON_MISC2 (in module ics), 39
REPORT_ON_MISC3 (in module ics), 39
REPORT_ON_MISC3_AIN (in module ics), 39
REPORT_ON_MISC4 (in module ics), 39
REPORT_ON_MISC4_AIN (in module ics), 39
REPORT_ON_MISC5 (in module ics), 39
REPORT_ON_MISC5_AIN (in module ics), 39
REPORT_ON_MISC6 (in module ics), 39
REPORT_ON_MISC6_AIN (in module ics), 39
REPORT_ON_PERIODIC (in module ics), 39
REPORT_ON_PWM_IN1 (in module ics), 39
request_enter_sleep_mode() (in module ics), 30
RequestEnterSleepMode() (in module ics), 18
reserved (ics.CyanSettings attribute), 5
RESERVED (ics.SWCanSettings attribute), 12
reserved0 (ics.OpEthGeneralSettings attribute), 9
reserved0 (ics.OpEthSettings attribute), 9
reserved_1 (ics.UartSettings attribute), 15
RESISTOR_OFF (in module ics), 39
RESISTOR_ON (in module ics), 39
rsvd (ics.EthernetSettings attribute), 5
RuntimeError, 1

S

SCRIPT_LOCATION_FLASH_MEM (in module ics), 39

SCRIPT_LOCATION_INTERNAL_FLASH (in module ics), [39](#)
SCRIPT_LOCATION_SDCARD (in module ics), [40](#)
SCRIPT_LOCATION_VCAN3_MEM (in module ics), [40](#)
SCRIPT_STATUS_RUNNING (in module ics), [40](#)
SCRIPT_STATUS_STOPPED (in module ics), [40](#)
ScriptClear() (in module ics), [18](#)
ScriptGetFBlockStatus() (in module ics), [18](#)
ScriptGetScriptStatus() (in module ics), [18](#)
ScriptLoad() (in module ics), [18](#)
ScriptReadAppSignal() (in module ics), [18](#)
ScriptReadRxMessage() (in module ics), [18](#)
ScriptReadTxMessage() (in module ics), [19](#)
ScriptStart() (in module ics), [19](#)
ScriptStartFBlock() (in module ics), [19](#)
ScriptStop() (in module ics), [19](#)
ScriptStopFBlock() (in module ics), [19](#)
ScriptWriteAppSignal() (in module ics), [19](#)
ScriptWriteRxMessage() (in module ics), [19](#)
ScriptWriteTxMessage() (in module ics), [19](#)
SerialNumber (ics.NeoDevice attribute), [8](#)
set_backup_power_enabled() (in module ics), [30](#)
set_context() (in module ics), [30](#)
set_device_settings() (in module ics), [30](#)
set_reflash_callback() (in module ics), [31](#)
set_rtc() (in module ics), [31](#)
SetBaudrate (ics.CanSettings attribute), [2](#)
SetBaudrate (ics.SWCanSettings attribute), [12](#)
SetReflashDisplayCallback() (in module ics), [20](#)
SetRTC() (in module ics), [19](#)
slaveVnetA (ics.CyanSettings attribute), [5](#)
slaveVnetB (ics.CyanSettings attribute), [5](#)
SLEEP_MODE (in module ics), [40](#)
SLOW_MODE (in module ics), [40](#)
spbrg (ics.Iso9141Keyword2000Settings attribute), [8](#)
spbrg (ics.LinSettings attribute), [8](#)
spbrg (ics.UartSettings attribute), [15](#)
SPY_PROTOCOL_BEAN (in module ics), [40](#)
SPY_PROTOCOL_CAN (in module ics), [40](#)
SPY_PROTOCOL_CANFD (in module ics), [40](#)
SPY_PROTOCOL_CGI (in module ics), [40](#)
SPY_PROTOCOL_CHRYSLER_CCD (in module ics), [40](#)
SPY_PROTOCOL_CHRYSLER_JPVW (in module ics), [40](#)
SPY_PROTOCOL_CHRYSLER_SCI (in module ics), [40](#)
SPY_PROTOCOL_CUSTOM (in module ics), [40](#)
SPY_PROTOCOL_DALLAS_1WIRE (in module ics), [40](#)
SPY_PROTOCOL_ETHERNET (in module ics), [40](#)
SPY_PROTOCOL_FLEXRAY (in module ics), [40](#)
SPY_PROTOCOL_FORD_UBP (in module ics), [40](#)
SPY_PROTOCOL_GENERIC_MANCHSESTER (in module ics), [40](#)
SPY_PROTOCOL_GENERIC_UART (in module ics), [40](#)
SPY_PROTOCOL_GM_ALDL_UART (in module ics), [40](#)
SPY_PROTOCOL_GME_CIM_SCL_KLINE (in module ics), [40](#)
SPY_PROTOCOL_GMFSA (in module ics), [40](#)
SPY_PROTOCOL_GMLAN (in module ics), [40](#)
SPY_PROTOCOL_I2C (in module ics), [40](#)
SPY_PROTOCOL_ISO9141 (in module ics), [40](#)
SPY_PROTOCOL_J1708 (in module ics), [40](#)
SPY_PROTOCOL_J1850PWM (in module ics), [40](#)
SPY_PROTOCOL_J1850VPW (in module ics), [40](#)
SPY_PROTOCOL_J1939 (in module ics), [40](#)
SPY_PROTOCOL_JTAG (in module ics), [40](#)
SPY_PROTOCOL_LIN (in module ics), [40](#)
SPY_PROTOCOL_MOST (in module ics), [40](#)
SPY_PROTOCOL_SENT_PROTOCOL (in module ics), [40](#)
SPY_PROTOCOL_SPI (in module ics), [40](#)
SPY_PROTOCOL_TCP (in module ics), [40](#)
SPY_PROTOCOL_UART (in module ics), [41](#)
SPY_PROTOCOL_UNIO (in module ics), [41](#)
SPY_STATUS2_CAN_HAVE_LINK_DATA (in module ics), [41](#)
SPY_STATUS2_CAN_ISO15765_LOGICAL_FRAME (in module ics), [41](#)
SPY_STATUS2_END_OF_LONG_MESSAGE (in module ics), [41](#)
SPY_STATUS2_ERROR_FRAME (in module ics), [41](#)
SPY_STATUS2_ETHERNET_CRC_ERROR (in module ics), [41](#)
SPY_STATUS2_ETHERNET_FCS_AVAILABLE (in module ics), [41](#)
SPY_STATUS2_ETHERNET_FRAME_TOO_SHORT (in module ics), [41](#)
SPY_STATUS2_ETHERNET_NO_PADDING (in module ics), [41](#)
SPY_STATUS2_ETHERNET_PREEMPTION_ENABLED (in module ics), [41](#)
SPY_STATUS2_FLEXRAY_NO_CRC (in module ics), [41](#)
SPY_STATUS2_FLEXRAY_NO_HEADERCRC (in module ics), [41](#)
SPY_STATUS2_FLEXRAY_TX_AB (in module ics), [41](#)
SPY_STATUS2_FLEXRAY_TX_AB_NO_A (in module ics), [41](#)
SPY_STATUS2_FLEXRAY_TX_AB_NO_B (in module ics), [41](#)
SPY_STATUS2_FLEXRAY_TX_AB_NO_MATCH (in module ics), [41](#)
SPY_STATUS2_GLOBAL_CHANGE (in module ics),

41
SPY_STATUS2_HAS_VALUE (in module `ics`), 41
SPY_STATUS2_HIGH_VOLTAGE (in module `ics`), 41
SPY_STATUS2_ISO_FRAME_ERROR (in module `ics`), 41
SPY_STATUS2_ISO_OVERFLOW_ERROR (in module `ics`), 41
SPY_STATUS2_ISO_PARITY_ERROR (in module `ics`), 41
SPY_STATUS2_LIN_ERR_MSG_ID_PARITY (in module `ics`), 41
SPY_STATUS2_LIN_ERR_RX_BREAK_NOT_0 (in module `ics`), 41
SPY_STATUS2_LIN_ERR_RX_BREAK_TOO_SHORT (in module `ics`), 41
SPY_STATUS2_LIN_ERR_RX_DATA_GREATER_8 (in module `ics`), 41
SPY_STATUS2_LIN_ERR_RX_SYNC_NOT_55 (in module `ics`), 41
SPY_STATUS2_LIN_ERR_TX_RX_MISMATCH (in module `ics`), 41
SPY_STATUS2_LIN_ID_FRAME_ERROR (in module `ics`), 41
SPY_STATUS2_LIN_NO_SLAVE_DATA (in module `ics`), 41
SPY_STATUS2_LIN_SLAVE_BYTE_ERROR (in module `ics`), 41
SPY_STATUS2_LIN_SYNC_FRAME_ERROR (in module `ics`), 41
SPY_STATUS2_LONG_MESSAGE (in module `ics`), 41
SPY_STATUS2_MOST_CHANGED_PAR (in module `ics`), 41
SPY_STATUS2_MOST_CONTROL_DATA (in module `ics`), 41
SPY_STATUS2_MOST_I2S_DUMP (in module `ics`), 42
SPY_STATUS2_MOST_LOW_LEVEL (in module `ics`), 42
SPY_STATUS2_MOST_MHP_CONTROL_DATA (in module `ics`), 42
SPY_STATUS2_MOST_MHP_USER_DATA (in module `ics`), 42
SPY_STATUS2_MOST_MOST150 (in module `ics`), 42
SPY_STATUS2_MOST_MOST50 (in module `ics`), 42
SPY_STATUS2_MOST_PACKET_DATA (in module `ics`), 42
SPY_STATUS2_MOST_STATUS (in module `ics`), 42
SPY_STATUS2_MOST_TOO_SHORT (in module `ics`), 42
SPY_STATUS2_RX_TIMEOUT_ERROR (in module `ics`), 42
SPY_STATUS2_VALUE_IS_BOOLEAN (in module `ics`), 42
SPY_STATUS3_CANFD_BRS (in module `ics`), 42
SPY_STATUS3_CANFD_ESI (in module `ics`), 42
SPY_STATUS3_CANFD_FDF (in module `ics`), 42
SPY_STATUS3_CANFD_IDE (in module `ics`), 42
SPY_STATUS3_CANFD_RTR (in module `ics`), 42
SPY_STATUS3_LIN_JUST_BREAK_SYNC (in module `ics`), 42
SPY_STATUS3_LIN_ONLY_UPDATE_SLAVE_TABLE_ONCE (in module `ics`), 42
SPY_STATUS3_LIN_SLAVE_DATA_TOO_SHORT (in module `ics`), 42
SPY_STATUS_ANALOG_DIGITAL_INPUT (in module `ics`), 42
SPY_STATUS_AUDIO_COMMENT (in module `ics`), 42
SPY_STATUS_AVSI_REC_OVERFLOW (in module `ics`), 42
SPY_STATUS_BAD_MESSAGE_BIT_TIME_ERROR (in module `ics`), 42
SPY_STATUS_BREAK (in module `ics`), 42
SPY_STATUS_BUS_RECOVERED (in module `ics`), 42
SPY_STATUS_BUS_SHORTED_GND (in module `ics`), 42
SPY_STATUS_BUS_SHORTED_PLUS (in module `ics`), 42
SPY_STATUS_CAN_BUS_OFF (in module `ics`), 42
SPY_STATUS_CAN_ERROR_PASSIVE (in module `ics`), 42
SPY_STATUS_CANFD (in module `ics`), 42
SPY_STATUS_CHECKSUM_ERROR (in module `ics`), 42
SPY_STATUS_COMM_IN_OVERFLOW (in module `ics`), 42
SPY_STATUS_CRC_ERROR (in module `ics`), 42
SPY_STATUS_EXPECTED_LEN_MISMATCH (in module `ics`), 42
SPY_STATUS_EXTENDED (in module `ics`), 42
SPY_STATUS_FLEXRAY_PDU (in module `ics`), 42
SPY_STATUS_FLEXRAY_PDU_NO_UPDATE_BIT (in module `ics`), 43
SPY_STATUS_FLEXRAY_PDU_UPDATE_BIT_SET (in module `ics`), 43
SPY_STATUS_GLOBAL_ERR (in module `ics`), 43
SPY_STATUS_GPS_DATA (in module `ics`), 43
SPY_STATUS_HEADERCRC_ERROR (in module `ics`), 43
SPY_STATUS_HIGH_SPEED (in module `ics`), 43
SPY_STATUS_INCOMPLETE_FRAME (in module `ics`), 43
SPY_STATUS_INIT_MESSAGE (in module `ics`), 43
SPY_STATUS_LIN_MASTER (in module `ics`), 43
SPY_STATUS_LOST_ARBITRATION (in module `ics`), 43
SPY_STATUS_MSG_NO_MATCH (in module `ics`), 43
SPY_STATUS_NETWORK_MESSAGE_TYPE (in module `ics`), 43
SPY_STATUS_REMOTE_FRAME (in module `ics`), 43

SPY_STATUS_TEST_TRIGGER (in module ics), 43
SPY_STATUS_TEXT_COMMENT (in module ics), 43
SPY_STATUS_TX_MSG (in module ics), 43
SPY_STATUS_TX_NOMATCH (in module ics), 43
SPY_STATUS_UNDEFINED_ERROR (in module ics), 43
SPY_STATUS_VSI_IFR_CRC_BIT (in module ics), 43
SPY_STATUS_VSI_TX_UNDERRUN (in module ics), 43
SPY_STATUS_XTD_FRAME (in module ics), 43
SpyMessage (class in ics), 12
SpyMessageJ1850 (class in ics), 13
StatusBitField (ics.SpyMessage attribute), 13
StatusBitField (ics.SpyMessageJ1850 attribute), 14
StatusBitField2 (ics.SpyMessage attribute), 13
StatusBitField2 (ics.SpyMessageJ1850 attribute), 14
StatusBitField3 (ics.SpyMessage attribute), 13
StatusBitField3 (ics.SpyMessageJ1850 attribute), 14
StatusBitField4 (ics.SpyMessage attribute), 13
StatusBitField4 (ics.SpyMessageJ1850 attribute), 14
stop_bits (ics.UartSettings attribute), 15
swcan (ics.FireSettings attribute), 7
swcan1 (ics.CyanSettings attribute), 5
swcan1 (ics.RadGalaxySettings attribute), 11
swcan2 (ics.CyanSettings attribute), 5
swcan2 (ics.RadGalaxySettings attribute), 11
SWCAN_AUTOSWITCH_DISABLED (in module ics), 43
SWCAN_AUTOSWITCH_DISABLED_RESISTOR_ENABLED (in module ics), 43
SWCAN_AUTOSWITCH_NO_RESISTOR (in module ics), 43
SWCAN_AUTOSWITCH_WITH_RESISTOR (in module ics), 43
SWCAN_SETTINGS_SIZE (in module ics), 43
SWCanSettings (class in ics), 11

T

tapPair0 (ics.OpEthGeneralSettings attribute), 9
tapPair1 (ics.OpEthGeneralSettings attribute), 9
tapPair2 (ics.OpEthGeneralSettings attribute), 9
tapPair3 (ics.OpEthGeneralSettings attribute), 9
tapPair4 (ics.OpEthGeneralSettings attribute), 9
tapPair5 (ics.OpEthGeneralSettings attribute), 9
termination_enables (ics.CyanSettings attribute), 5
text_api (ics.CyanSettings attribute), 5
text_api (ics.FireSettings attribute), 7
text_api (ics.RadGalaxySettings attribute), 11
TextApiSettings (class in ics), 14
time_500us (ics.Iso9141Keyword2000InitSteps attribute), 8
TimeHardware (ics.SpyMessage attribute), 13
TimeHardware (ics.SpyMessageJ1850 attribute), 14
TimeHardware2 (ics.SpyMessage attribute), 13
TimeHardware2 (ics.SpyMessageJ1850 attribute), 14
TimeStampHardwareID (ics.SpyMessage attribute), 13
TimeStampHardwareID (ics.SpyMessageJ1850 attribute), 14
TimeStampSystemID (ics.SpyMessage attribute), 13
TimeStampSystemID (ics.SpyMessageJ1850 attribute), 14
TimeSystem (ics.SpyMessage attribute), 13
TimeSystem (ics.SpyMessageJ1850 attribute), 14
TimeSystem2 (ics.SpyMessage attribute), 13
TimeSystem2 (ics.SpyMessageJ1850 attribute), 14
TqProp (ics.CanSettings attribute), 2
TqProp (ics.SWCanSettings attribute), 12
TqSeg1 (ics.CanSettings attribute), 2
TqSeg1 (ics.SWCanSettings attribute), 12
TqSeg2 (ics.CanSettings attribute), 2
TqSeg2 (ics.SWCanSettings attribute), 12
TqSync (ics.CanSettings attribute), 2
TqSync (ics.SWCanSettings attribute), 12
transceiver_mode (ics.CanSettings attribute), 3
transceiver_mode (ics.SWCanSettings attribute), 12
transmit_messages() (in module ics), 31
TxMessages() (in module ics), 20

U

uart (ics.FireSettings attribute), 7
uart2 (ics.FireSettings attribute), 7
UART_SETTINGS_SIZE (in module ics), 43
UARTSettings (class in ics), 15
ucConfigMode (ics.OpEthSettings attribute), 9
ucInterfaceType (ics.OpEthGeneralSettings attribute), 9
USE_TQ (in module ics), 43

V

validate_hobject() (in module ics), 32
ValidateHObject() (in module ics), 20
Vcan3Settings (class in ics), 15
VcanRFSettings (class in ics), 15
vnetBits (ics.FireSettings attribute), 7
VNETBITS_FEATURE_ANDROID_MSGS (in module ics), 43
VNETBITS_FEATURE_DISABLE_USB_CHECK (in module ics), 43

W

write_sdcard() (in module ics), 32